



# Latitude 14 Rugged

# Summary of Independent Environmental Testing

## General information

**Tests performed** MIL-STD-810G testing  
IEC ingress testing  
UL and CE safety testing / ESD, emissions, immunity testing

---

**Equipment tested** Latitude 14 Rugged / 5404 / P46G

---

**Independent testing facilities** **SGS Taiwan Ltd.**  
31, Wu Chyuan Road, New Taipei Industrial Park, Wu Ku District

**SGS USA Ltd. - Environ Laboratories LLC.**  
9725 Girard Avenue, South Minneapolis, MN 55431

**Professional Testing Inc.**  
1601 North A.W. Grimes Blvd., Suite B, Round Rock, TX 78665

**UL Taiwan Ltd.**  
1/F, 260, Da-Yeh Road, Peitou, Taipei City, Taiwan 112

**UL China Ltd.**  
**Office:** Building A1, 1F & 2F, Nansha Science and Technology Innovation Center,  
No. 25, South Huanshi Avenue, Nansha District, Guangzhou 511458, China  
**Lab:** 163 Ping Yun Rd., West Of HuangPu Ave, Guangzhou, P. R. China, 510656

**UL Taiwan Ltd.**  
1/F, 260, Da-Yeh Road, Peitou, Taipei City, Taiwan 112

---

## Notes

All environmental testing listed in the accompanying tables was performed and reported independently by the accredited testing companies listed above.

Documented MIL-STD-810G, IEC, UL, emissions, immunity and ESD testing guidelines were followed. All tests were performed with I/O and expansion doors closed, unless otherwise noted. A summary listing of tests appear in the tables included in this document.

## MIL-STD-810G environmental testing

Test name	Test procedure	Description	Operational	Result
Altitude - Storage / Air transport	MIL-STD-810G, Method 500.5, Procedure I	Chamber at 30,000ft for 1 hour	No	Pass
Altitude - Operational / Air carriage	MIL-STD-810G, Method 500.5, Procedure II	Chamber at 15,000ft for 1 hour	Yes	Pass
High temperature - Storage	MIL-STD-810G, Method 501.5, Procedure I	<b>160°F (71°C)</b> - 7 day exposure (7x 24hr cycles).	No	Pass
High temperature - Operational	MIL-STD-810G, Method 501.5, Procedure II	<b>140°F (60°C)</b> - 5 day exposure (5x 24hr cycles)	Yes	Pass
High temperature - Tactical standby to operational	MIL-STD-810G, Method 501.5, Procedure III	<b>158°F (70°C) to 140°F (60°C)</b> - Unit is presoaked at high temperature for 2 hours after temperature stabilization. Temperature is ramped to lower temperature and operational test is performed	Both	Pass
Low temperature - Storage	MIL-STD-810G, Method 502.5, Procedure I	<b>-60°F (-51°C)</b> - 24 hour exposure	No	Pass
Low temperature - Operational	MIL-STD-810G, Method 502.5, Procedure II	<b>-20°F (-29°C)</b> - 24 hour exposure	Yes	Pass
Thermal shock	MIL-STD-810G, Method 503.5, Procedure I	<b>-60°F (-51°C) to 160°F (71°C)</b> - Cyclic temperature exposure with 3 shocks; unit is not operating with functional test between cycles	No	Pass
Humidity - Aggravated	MIL-STD-810G, Method 507.5, Procedure II	0% to 95% - non-condensing humidity - ten 24-hour cycles - temperature cycled between 86°F (30°C) and 140°F (60°C); relative humidity maintained at 95%	No	Pass
Sand and dust - Blowing dust	MIL-STD-810G, Method 510.5, Procedure I	Particle density: 10.6 +/- 7 g/m <sup>3</sup> . Air velocity: 8.9 +/- 1.3 m/s Operating temperature of 140°F (60°C).	Yes	Pass
Sand and dust - Blowing sand	MIL-STD-810G, Method 510.5, Procedure II	Sand density: 2.2 g/m <sup>3</sup> . Air Velocity: 18 - 29 m/s. Operating temperature of 140°F (60°C).	Yes	Pass
Vibration - Minimum integrity test	MIL-STD-810G, Method 514.6, Procedure I, Category 24	Category 24 - Figure 514.6E-1 - power spectral density = 0.04g <sup>2</sup> /Hz at 20Hz -1000Hz, -6dB/Octive at 1000Hz - 2000Hz; 60 minutes x 3 axes; unit is not operating during tests; functional test after each axis	No	Pass
Vibration - Composite wheeled vehicle	MIL-STD-810G, Method 514.6, Procedure I, Category 4	Category 4 - Figure 514.6C-3	No	Pass
Vibration - Ground vehicle	MIL-STD-810G, Method 514.6, Procedure I, Category 4	Category 4 - Figure 514.6C-1	Yes	Pass
Vibration - Loose cargo	MIL-STD-810G, Method 514.6, Procedure II	1" peak to peak orbital motion at 5 Hz	No	Pass



Test name	Test procedure	Description	Operational	Result
<b>Shock - Functional shock</b>	MIL-STD-810G, Method 516.6, Procedure I	40g, 11ms, saw-tooth, 3 shocks +/- per axis, 3 axes; unit is operating	Yes	Pass
<b>Shock - Materials to be packaged</b>	MIL-STD-810G, Method 516.6, Procedure II	30g, 304 ips square wave shock; 1 shocks/axis/direction for a total of 6 shocks; unit is non-operational during test	No	Pass
<b>Shock - 36" transit drop</b>	MIL-STD-810G, Method 516.6, Procedure IV	36" (3', 0.91m) drops to 2" of plywood over concrete; one drop to each face, edge and corner; unit is closed and not operating; 26 total drops on a single test unit	No	Pass
<b>Shock - Crash hazard</b>	MIL-STD-810G, Method 516.6, Procedure V	185g, 2ms half sine; 2 shocks/axis/direction for a total of 12 shocks; unit is non-operational during test	No	Pass
<b>Shock - Bench handling</b>	MIL-STD-810G, Method 516.6, Procedure VI	Angle drops onto solid wooden bench thickness least 4.25cm (1.675 inch). Test height judgment as two conditions as rise test units at one edge 100mm (4 inch) or rise an angle of 45° about a solid wooden bench top, whichever is less. Unit is operational during test.	No	Pass
<b>Freeze/thaw - Rapid temperature change</b>	MIL-STD-810G, Method 524, Procedure III	Unit stabilized at 77°F (25°C) and relative humidity of 97% for 1 hour, then transferred rapidly to a freezing chamber at 14°F (-10°C); unit is allowed to stabilize plus one additional hour; unit is brought back to above-freezing test; unit is not operating during the test with operational test performed at the end of cycles	No	Pass

## IEC ingress protection

Test name	Test procedure	Description	Operational	Result
<b>Dust ingress protection</b>	IEC 60529, IP-5x	<b>IP-5x</b> - Ingress of dust is not entirely prevented, but it must not enter in sufficient quantity to interfere with the satisfactory operation of the equipment; complete protection against contact; unit is not operating	No	Pass
<b>Water ingress protection</b>	IEC 60529, IP-x2	<b>IP-x2</b> - Vertically dripping water shall have no harmful effect when the enclosure is tilted at an angle up to 15° from its normal position; unit is not operating	No	Pass



## Emissions and safety

Test name	Test procedure	Description	Operational	Result
<b>Conducted and radiated emissions</b>	EN55022: 2010 ANSI C63.4-2003 FCC 47 CFR Part 15, Class B	Radiated and conducted emission measurements and limits for Information Technology Equipment (ITE). Testing performed with doors open, cables attached.	Yes	Pass
<b>Electrostatic discharge, various conducted and radiated immunity</b>	EN55024: 2010 ANSI C63.4-2003	EN 61000-3-2, EN 61000-3-3, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6, EN 61000-4-8, EN 61000-4-11 Testing performed with doors open, cables attached.	Yes	Pass
<b>Safety</b>	UL/IEC mark - 60950	UL/IEC mark		Pass

## Other testing

Test name	Test procedure	Description	Operational	Result
<b>Vehicle vibration</b>	ASTM D4169-04 (99), Schedule E, Truck Assurance Level II	1-200Hz, 0.52grms in all three axis; 90 minutes per axis	Yes	Pass

## Pass criteria and test scope information

For operational tests, a pass indicates that the unit remained operational during the entirety of the test. For non-operational tests, a pass indicates that a functional verification was performed immediately after the test exposure, in which the unit was powered on and booted to the primary operating system. Cosmetic damage does not constitute a failure unless there is a safety concern. Sample sizes tested are not statistically significant.

<sup>1</sup> Based on testing and certification to MIL-STD-810G and IEC 60529 (IP-65) standards, performed and reported independently by accredited testing companies.

