

# DELL PDU



The sturdy, reliable Power Distribution Units (PDUs) are deployed with a rack enclosure to distribute power to IT equipment.

## FULL-LINE OF TRUSTED PDUS
















Dell's family of power distribution units, Dell PDUs, utilize a combination of worldwide standard IEC power outlet connections with regionalized input options allowing flexibility across a variety of global power infrastructures. Detachable inlet cords on most models facilitate interconnection of various models, providing a wide selection of deployment options. Individual models have multiple outlets, and combining models can increase outlet counts from 16-to-24 useable outlets per available power circuit.


















## MOUNTING CHOICES OF 0U/1U IDEAL FOR DELL 4210 AND 2410 RACK ENCLOSURES

The 0U/1U models feature an innovative tool-less mounting bracket to provide quick and easy placement into the 0U space of Dell racks (recommended for the Dell 4210 racks), helping to maximize available rack space for systems and reduce overall installation time. Additionally, the 0U/1U models ship with a set of brackets enabling them to be mounted in a 1U space of a rack enclosure.

## ADDITIONAL HALF-HEIGHT FORM FACTORS FOR DELL 4220 AND 2420 RACK ENCLOSURES

The Half-Height PDUs are built to mount in the rear of the Dell 4220 racks (these PDUs are not compatible with the Dell 4210 racks). The sensible design makes the PDU outlet more easily reachable while not taking up the rack U-space.

NORTH AMERICA						
Description	Input Circuit	Input Plug Type	Input Circuit	Output Receptacles		Cord Length, ft.
0U/1U, 100-120V, 15A, (5) 5-15	120V	15A	C14 Inlet		(5)5-15	n/a*
0U/1U, 120-240V/15A, 220-240V/10A, (8) C13	120V	15A	C14 Inlet		(8)C13	n/a*
Half Height, 100-120V, 20A, (12) 5-15	120V	20A	C20 Inlet		(12)5-15	n/a*
0U/1U, 100-240V/20A, 220-240V/16A, (13) C13	120V	20A	C20 Inlet		(13)C13	n/a*
0U/1U, 100-240V/20A, 220-240V/16A, (7) C13, (2) C19	120V	20A	C20 Inlet		(7)C13, (2)C19	n/a*
Half Height, 100-240V/20A, 220-240V/16A, (14) C13	120V	20A	C20 Inlet		(14)C13	n/a*
0U/1U, 120V, 30A, (4) C19	120V	30A	L5-30P		(4)C19	12
0U/1U, 120-240V/15A, 220-240V/10A, (8) C13	200-240V	15A	C14 Inlet		(8)C13	n/a*
0U/1U, 100-240V/20A, 220-240V/16A, (13) C13	200-240V	20A	C20 Inlet		(13)C13	n/a*
Half Height, 100-240V/20A, 220-240V/16A, (14) C13	200-240V	20A	C20 Inlet		(13)C13	n/a*
0U/1U, 100-240V/20A, 220-240V/16A, (7) C13, (2) C19	200-240V	20A	C20 Inlet		(7)C13, (2)C19	n/a*
Half Height, 200-208V, 30A, (14) C13, (2) C19	200-240V	30A	L6-30P		(14)C13, (2) C19	10
0U/1U, 208V, 30A, (4) C19	200-240V	30A	L6-30P		(4)C19	12
0U/1U, 208V, 60A, (3) C19	200-240V	60A	IEC309 60A		(3)C19	12
0U/1U, 208V, 8.6kW, (3) C19	208V 3PH	30A, 3PH	L15-30P		(3)C19	12

INTERNATIONAL							
Description		Input Circuit	Input Plug Type	Output Receptacles		Cord Length, ft.	Dell P/N
0U/1U, 120-240V/15A, 220-240V/10A, (8) C13	220-240V	10	C14 Inlet		(8)C13	n/a*	J541N
0U/1U, 100-240V/20A, 220-240V/16A, (13) C13	220-240V	16	C20 Inlet		(13)C13	n/a*	K558N
0U/1U, 100-240V/20A, 220-240V/16A, (7) C13, (2) C19	220-240V	16	C20 Inlet		(7)C13 (2)C19	n/a*	G789N
Half Height, 100-240V/20A, 220-240V/16A, (14) C13	220-240V	16	C20 Inlet		(14)C12	n/a*	J544N
0U/1U, 220-240V, 32A, (4) C19, EMEA/ASIA	220-240V	32	IEC309 32A		(4)C19	12	K562N
0U/1U, 220-240V, 63A, (3) C19	220-240V	63	IEC309 63A		(3)C19	12	K579N
0U/1U, 240V, 32A, (4) C19, AUS	220-240V	32 (Australia)	Clipsal 56P332 equivalent		(4)C19	12	G795N
0U/1U, 220-240V, 32A, (4) C19, CHN	220-240V	32 (China)	Hardwire		(4)C19	12	H588N
0U/1U, 400V, 22kW, (3) C19	400V 3PH	32A, 3PH	IEC309 32A-3PH		(3)C19	12	J559N
JAPAN							
Description		Input Circuit	Input Plug Type	Output Receptacles		Cord Length, ft.	Dell P/N
0U/1U, 100-120V, 15A, (5) 5-15	100V	15A	C14 Inlet		(5)5-15	n/a*	G761N
Half Height, 100-120V, 20A, (12) 5-15	100V	20A	C20 Inlet		(12)5-15	n/a*	H553N
0U/1U, 100-240V/20A, 220-240V/16A, (13) C13	100V	20A	C20 Inlet		(13)C13	n/a*	K558N
0U/1U, 100-240V/20A, 220-240V/16A, (7) C13, (2) C19	100V	20A	C20 Inlet		(7)C13, (2)C19	n/a*	G789N
Half Height, 100-240V/20A, 220-240V/16A, (14) C13	100V	20A	C20 Inlet		(14)C13	n/a*	J544N
0U/1U, 100-240V/20A, 220-240V/16A, (13) C13	200V	20A	C20 Inlet		(13)C13	n/a*	K558N
Half Height, 100-240V/20A, 220-240V/16A, (14) C13	200V	20A	C20 Inlet		(13)C13	n/a*	J544N
0U/1U, 100-240V/20A, 220-240V/16A, (7) C13, (2) C19	200V	20A	C20 Inlet		(7)C13, (2)C19	n/a*	G789N
Half Height, 200-208V, 30A, (14) C13, (2) C19	200V	30A	L6-30P		(14)C13, (2)C19	10	K559N

Dell cannot be responsible for errors in typography or photography.

