



Dell PowerVault Tape Automation

	PowerVault 124T Tape Autoloader	PowerVault TL2000	PowerVault TL4000
	up to 24TB (native)	up to 36TB (native)	up to 72 TB (native)
	Entry-level tape automation for large servers or small workgroups	Network backup or entry-level SAN backup	

Features							
Drive Type)	LTO-3-060	LTO-3	LTO-4	LTO-5	LTO-3-060, LTO-3, LTO-4 and LTO-5	LTO-3-060, LTO-3, LTO-4 and LTO-5	
Number of Drives	1				1 or 2	Up to 4	
Number of Cartridges	8 or 16				24	48	
Import/Export Slots	0				1	3	
Form Factor	2U				2U	4U	
Chassis	Desktop or Rackmount				Rackmount (desktop conversion kit included)		
Media	LTO-1 (read only), LTO-2, LTO-3, LTO-3 WORM	LTO-1 (read only), LTO-2, LTO-3, LTO-3 WORM	LTO-2 (read only), LTO-3, LTO-3 WORM, LTO-4, LTO-4 WORM	LTO-3 and LTO-3 WORM (Read Only), LTO-4, LTO-4 WORM, LTO-5, LTO-5 WORM	LTO3 and LTO3-060: LTO-1 (Read Only), LTO-2, LTO-3, LTO-3 WORM LTO4:LTO-2 (Read Only), LTO-3, LTO-3 WORM, LTO-4, LTO-4 WORM LTO5:LTO-3 and LTO-3 WORM (Read Only), LTO-4, LTO-4 WORM, LTO-5, LTO-5 WORM		
Max Capacity ¹	Up to 6.4TB	Up to 6.4TB	Up to 12.8TB	Up to 24 TB	Up to 19.2TB	Up to 38.4TB	
Max Backup Rate ²	60MB/sec, 216GB/hr	Up to 80MB/sec 288GB/hr	120MB/sec 432GB/hr	140MB/sec 504GB/hr	LTO-3-060: 60MB/s, 216GB/hr LTO-3: 80MB/s, 288GB/hr LTO-4-120: 120MB/s, 432GB/hr LTO-5-140: 140MB/s, 504GB/hr		
Interface	Ultra 160 LVD, 3Gb SAS or 6Gb SAS				Ultra 160 LVD, 3Gb SAS, 6Gb SAS, 4Gb/s FC, 8Gb/s FC, 1Gb iSCSI		
Software Supported	Support leading backup applications from Computer Associate Arcserve™, Symantec Backup Exec™, and CommVault Galaxy™						
Library Managed Encryption	Available on PowerVault ML6000, PowerVault TL4000, and PowerVault TL2000 configured with LTO-4 drive(s) and LTO-5 drives						
Included Services	Limited Warranty ³ , 30-Day Getting Started Phone Support ⁴ , E-support, and Next Business Day On-Site Service ⁵						

PowerVault ML6000 Tape Libraries ⁶						
Scalability to a maximum of 613.5TB (native) ¹						
Scalable SAN Backup Base models will scale to full 41U with addition of ML6000 ⁶ EM (9U expansion modules)						
Features	ML6010	ML6020	ML6030	ML6000EM	32U (ML6030 + 1 ML6000 EM)	41U (ML6030 + 2 ML6000 EM)
Drive Type	LTO-3, LTO-4, LTO-5					
Number of Drives	1 or 2	1 to 6	1 to 10	1 to 4	1 to 14	1 to 18
Number of Cartridges	41	133	225	46 or 92	317	409
Import/Export Slots	6	6, 12, or 18	6, 12, 18, 24, or 30	6	6, 12, 18, 24, 30, 36, or 42	6, 12, 18, 24, 30, 36, 42, 48, or 52
Form Factor	5U	14U	23U	9U	32U	41U
Chassis	Rackmount					
Media	LTO3: LTO-1(Read Only), LTO-2, LTO-3, LTO-3 WORM LTO4: LTO-2(Read Only), LTO-3, LTO-3 WORM, LTO-4, LTO-4 WORM LTO5: LTO-3 and LTO-3 WORM (Read Only), LTO-4, LTO-4 WORM, LTO-5, LTO-5 WORM					
Max Capacity ¹	61.5TB	199.5TB	337.5TB	138TB	475.5TB	613.5TB
Max Backup Rate ²	Up to 280MB/s, 1008GB/hr	Up to 840MB/s, 3024GB/hr	Up to 1,400MB/s, 5040GB/hr	Up to 560MB/s, 2016GB/hr	Up to 1960MB/s, 7056GB/hr	Up to 2520MB/s, 9072GB/hr
Interface	Ultra 160 LVD, 3Gb SAS, 6Gb SAS, 4Gb/s FC, 8Gb/s FC					
Software Supported	Dell™ Tape Backup Software: Symntec Backup Exec™, CommVault Galaxy™, Computer Associate Arcserve™					
Library Managed Encryption	Available on PowerVault ML6000, PowerVault TL4000, and powerVault TL2000 With LTO-4 drive(s) and LTO-5 drives)					
Included Services	Limited Warranty ³ , 30-Day Getting Started Phone Support ⁴ , and Next Business Day On-Site Service ⁵					

¹ 1 GB means 1 billion bytes and TB means 1 trillion bytes. Actual capacity varies with preloaded material and operating environment and will be less.

² Actual performance is dependent on settings, user environment and applications.

³ For a complete copy of our guarantees or limited warranties, please visit <http://www.dell.com/warranty> or write to Dell USA L.P., One Dell Way, Round Rock, Texas 78682, Attn: Warranties.

⁴ Telephone support provides help with installation, optimization and configuration questions during the critical 30-day period after shipment of your systems.

⁵ Service may be provided by a third party. Technician will be dispatched if necessary in parallel with phone-based troubleshooting for severity level 1 issues on systems with ProSupport Mission Critical or Same Day Response service. Technician will be dispatched if necessary following phone-based troubleshooting for all other severity levels and on-site response service levels. Repair time is measured from dispatch time of the on-site response service. Subject to parts availability, geographical restrictions and terms of service contract. Service timing dependent upon time of day call placed to Dell. U.S. only.

⁶ Yosemite is not available on the ML6000 control modules.

Dell cannot be responsible for errors in typography or photography. Dell disclaims proprietary interest in the marks and names of others. PowerVault is a trademark of Dell Inc. ©2008 Dell Inc. All rights reserved. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Reproduction in any manner whatsoever without the express written permission of Dell Inc. is strictly forbidden. For more information contact Dell.

Simplify your network at Dell.com/storage

