

Dell Networking S5000

Modular 1RU 10/40GbE and FC 2/4/8 switch

High-density 1RU 1/10GbE or 2/4/8G FC modules with four fixed 40GbE uplinks and low latency for line-rate performance, feature-rich layer 2/3 and storage networking for iSCSI, FC/FCoE and RoCE.

The Dell S5000 1RU Ethernet switch offers innovative modular, converged networking capabilities. The switch converges LAN and SAN traffic over a single 10GbE connection to help optimize server and storage connectivity in enterprise-scale data centers deploying separate networks based on different networking protocols.

Converged LAN/SAN ToR switch

The Dell S5000 is a 10/40GbE switch architected for a ToR virtualized data center environment. It provides a fully modular converged LAN/SAN switch purpose-built for applications in high-performance data center and fabric deployments. The S5000 supports LAN and native Fibre Channel ports using optional modules for maximum flexibility and scalability.

Leveraging a non-blocking, cut-through switching architecture, the S5000 provides line-rate L2 and L3 forwarding capacity with low latency to maximize network performance. The S5000 is a fully modular switch with four modular bays and four fixed 40GbE uplink ports. Each 40GbE QSFP+ uplink can also support four 10 GbE ports using a breakout cable. The S5000 supports three types of modules, including a Unified port module with 12 configurable ports for Fibre Channel 2/4/8Gbps and/or 1/10GbE SFP+, as well as SFP+ or 1/10GBASE-T Ethernet modules, each providing 12 1/10GbE ports.

The S5000 is powered by the industry-hardened, feature-rich Dell Networking OS9 (OS9) designed for maximum dependability and uptime. Virtual link trunking (VLT) provides a loop-free topology with active-active load-sharing of links from access to core. Hardware stacking using front port stacking up to six units provides maximum flexibility and scalability for data center environments. The S5000 supports Dell Open Automation Framework, which provides advanced network automation and virtualization capabilities for virtual data center environments. The Open Automation Framework is comprised of a suite of interrelated network management tools which can be used together or independently to provide a more flexible, available and manageable network while helping to reduce operational expenses.

Key applications

- Lossless fabric for LAN/SAN deployments
- Design with the Dell Z Series core switch to create a flat, two-tier, non-blocking 1/10/40GbE data center network design
- Design a Clos fabric with S5000 switch in leaf and spine with the S Series 1/10GbE Ethernet switches for cost-effective aggregation of 10GbE uplinks
- Design with Dell N Series switches to create a modern campus network with pay-as-you-grow expansion capability or consolidate campus aggregation and small data center functionality

- High-performance SDN/OpenFlow 1.3 enabled with ability to inter-operate with industry standard OpenFlow controllers
- 1/10GBase-T and SFP+ modules available on the same ToR switch

Key features

- OS9 offers inherent stability as well as advanced monitoring and serviceability functions
- Open Automation Framework adds VM-awareness as well as automated configuration and provisioning capabilities to simplify the management of virtual network environments
- Scalable L2 and L3 Ethernet switching with QoS and a full complement of standards-based IPv4 and IPv6 features
- VLT and mVLT for layer 2 multipath
- User port stacking support for up to six units
- Support for jumbo frames for high-end server connectivity
- 128 link aggregation groups with up to eight members per group, using advanced hashing
- Fibre Channel, FCoE, FCoE transit (FIP Snooping) and NPV Proxy Gateway (NPG), Fibre Channel Forwarding (FCF)
- Full data center bridging (DCB) support for lossless iSCSI SANs, RoCE and converged network.
- Redundant, hot-swappable power supplies and fans
- I/O panel to PSU airflow or PSU to I/O panel airflow (reversible airflow)
- VRF-lite enables sharing of networking infrastructure and provides L3 traffic isolation across tenants
- 16, 28, 40, 52, 64 10GbE ports available

A modular, compact form-factor switch optimized for LAN and SAN convergence and easy 1GbE to 10GbE migration

Dell S5000 overview

Server virtualization and cloud-based deployment models are increasing IT organizations' productivity while improving their ability to respond to continuously changing business needs. However, the rate at which the technology is evolving is forcing IT departments to invest in solutions that are flexible, future-ready and cost-effective.

The Dell S5000 is a high-density 1RU switch that offers innovative flexibility due to its unique modular architecture. S5000 is well suited for data center access and aggregation layer deployments for physical and virtual servers and LAN and SAN convergence over lossless fabrics.

- 1RU high-density switch with four module slots and four fixed 40GbE (QSFP+) uplinks (totaling 64 10GbE ports with breakout cables)
- Three optional modules are SFP+ Ethernet, 1/10GBase-T Ethernet, and a Unified Module supporting Fibre Channel and/or SFP+ Ethernet. The Ethernet modules support 12 1/10GbE ports and the Unified Module supports up to 12 FC 2/4/8Gbps and/or 12 1/10GbE ports.
- 1.28Tbps (full-duplex) non-blocking, cut-through switching fabric delivers line-rate performance
- FCoE, iSCSI and RDMA over Converged Ethernet (RoCE) is supported on all Ethernet ports

S5000 I/O module options



Ethernet modules (above) provide 12 1/10GbE ports using SFP+ (left) or 1/10GBASE-T (right) interfaces. The Ethernet modules support Ethernet-based LAN traffic and Ethernet-based SAN traffic for FCoE and iSCSI, and RoCE.



Unified port module (above) provides up to 12 ports for 2/4/8Gbps native Fibre Channel using SFP+/SFP interface. The unified port module supports Fibre Channel-based SAN traffic as well as up to 12 FC 2/4/8 and/or 12 1/10GbE ports.

Deployment models for S5000

Dell S5000 supports deployment models for small campus core or traditional, virtualized and converged data centers.




Figure 1. Campus deployment models for S5000

The flexibility of scale and types of ports offered by the S5000 make it an attractive choice for small campus core switches. Customers have the ability to connect legacy or new 1GbE switches to S5000 using 1GbE or 10GbE uplinks. Many small campuses also have a mini data center deployed within the wiring closet. In these environments, IT staff are forced to either deploy multiple switches to meet the needs of servers and storage in the wiring closet or try to fit server and storage workloads in the campus networks. With the S5000, customers have the ability to install the types of modules that best meets the needs of campus and data center workloads in the wiring closet.

Traditional Ethernet deployments




Figure 2. Redundant connections from 10GbE rack and blade servers deployed in a traditional Ethernet environment

Each server rack in this deployment model contains two S5000 switches offering redundant 10GbE connections to each server. The switches may be deployed as stand-alone switches or stacked for management simplification. Typical stacking configurations include a pair of stacked switches in each rack or two stacks of switches extending horizontally across multiple switches. In a typical single high-density server rack with redundant connections, up to 48 Dell PowerEdge rack servers or up to 96 PowerEdge Blades can be connected to a pair of S5000 in a single rack.





Figure 3. Large-scale 1GbE server connections

Servers with 1GbE redundant ports are connected to a pair of Dell Networking S55 or S60 1GbE switches. Using 10GbE up link connections, S55 or S60 leaf switches are connected to a pair of S5000 spine switches to form a large access layer fabric. In a typical high-density server configuration with redundant connections, up to 576 1GbE (1152 if redundancy not required) servers can be connected to a pair of S5000 switches through 24 Dell S55 or S60 switches.




1/10GbE Rack Servers and Storage

Figure 4. 1/10GbE rack servers in a virtualized data center

Virtual Link Trunking (VLT) is a Dell Networking multi-path solution to create a dynamic or static LAG that terminates on two different VLT-enabled physical switches. VLT is a dual active control plane implementation of multi-system LAG. VLT creates a single logical view of the two physical switches for the node at the other end.

In a virtualized data center, each server can transmit a significant amount of data easily overwhelming a traditional network infrastructure. VLT-based network infrastructure provides active-active connections from the server expanding the available bandwidth while increasing network resiliency. In a typical high-density server configuration with redundant connections, up to 1188 1/10GbE servers can be connected to a pair of Z9500 switches through 66 S5000 switches.



10GbE Blade Servers and Storage

Figure 5. 10GbE blade servers in a virtualized data center

For organizations creating the next-generation architecture for their information technology, meeting performance requirements for critical workloads is paramount. Dell blade solutions combine high-speed connectivity in the form of the backplane of the Dell PowerEdge M1000e blade enclosure with the compute density of Dell blade servers. The MXL/IOA switch for M1000e blade enclosure is a 40GbE capable, modular and stackable blade switch.

In a typical high-density server configuration with redundant connections, up to 4752 10GbE servers can be connected to a pair of Z9500 switches through 58 S5000 switches.




Figure 6. M1000e comparisons showing East/West traffic advantage

Modern data centers are going through a dramatic shift of traffic patterns from mostly north-south to mostly east-west traffic. Dell solutions with local switching capabilities help ensure that server to server traffic will take the least amount of hops, which can significantly enhance application performance.

LAN and SAN convergence

Organizations can take advantage of LAN/SAN convergence by deploying Internet Small Computer System Interface (iSCSI), Fibre Channel over Ethernet (FCoE), or even both network fabrics, on the DCB-enabled network. These technologies allow IT organizations to leverage a single, lossless and converged Ethernet network to enable LAN and SAN convergence.




Figure 7. Lossless converged LAN and iSCSI SAN

A typical architecture will connect Dell PowerEdge rack servers directly to S5000 or M1000e blade servers through MXL/IOA blade switches to S5000. Such architecture reduces the number of server and switch optics, fiber optic cables, and number of ToR switches in the data center. This approach can result in simplification of I/O, reduced capital and operational costs, and improved IT staff productivity.




Figure 8. Lossless converged LAN and FCoE SAN

S5000 consolidates LAN and SAN networks on one physical network infrastructure while providing logical separation of LAN and SAN traffic in the network. This approach helps ensure organizations are able to connect to existing FC SANs for non-stop and optimal IT operations while extending the advantages associated with LAN and SAN convergence. A typical architecture will connect Dell PowerEdge rack servers directly to S5000 or M1000e blade servers through MXL/IOA blade switches to S5000.

S5000 acts as an FCF offering direct connectivity to FC storage or as an NPG, offering connectivity between servers and FC SANs. Using 10GbE Converged Network Adapters (CNAs) servers are able to connect to S5000 using FCoE capability. Up to 12 ports on S5000 can be configured for native Fibre Channel connectivity to FC storage, servers or SANs. All Ethernet ports can be connected to FCoE servers.

Specifications: Dell S5000 unified storage Ethernet switch

Ordering Information

S5000

1RU, LAN/SAN Converged Switch, 4x40GbE QSFP+, 4 Modular Bays with 2x AC PSU, 2x Fan Modules, I/O to PSU Airflow, 4-Post Rack Mount Kit

1RU, LAN/SAN Converged Switch, 4x40GbE QSFP+, 4 Modular Bays with 2x AC PSU, 2x Fan Modules, PSU to I/O Airflow, 4-Post Rack Mount Kit

1RU, LAN/SAN Converged Switch, 4x40GbE QSFP+, 4 Modular Bays with 2x DC PSU, 2x Fan Modules, I/O to PSU Airflow, 4-Post Rack Mount Kit

1RU, LAN/SAN Converged Switch, 4x40GbE QSFP+, 4 Modular Bays with 2x DC PSU, 2x Fan Modules, PSU to I/O Airflow, 4-Post Rack Mount Kit

1RU, LAN/SAN Converged Switch, 4x40GbE QSFP+, 4 Modular Bays with 2x AC PSU, 2x Fan Modules, I/O to PSU Airflow, 4-Post Rack Mount Kit, TAA

1RU, LAN/SAN Converged Switch, 4x40GbE QSFP+, 4 Modular Bays with 2x AC PSU, 2x Fan Modules, PSU to I/O Airflow, 4-Post Rack Mount Kit, TAA

Power Supplies

S5000, AC Power Supply, I/O to PSU Airflow, 100–240V, 750W

S5000, AC Power Supply, PSU to I/O Airflow, 100–240V, 750W

S5000, DC Power Supply, I/O to PSU Airflow, -48 to -60V, 1100W

S5000, DC Power Supply, PSU to I/O Airflow, -48 to -60V, 1100W

Fans

S5000, Fan Module, I/O to PSU airflow

S5000, Fan Module, PSU to I/O airflow

Service Side Kits

S5000, Service Side Kit, 2x AC PSU, 2x Fan Modules, I/O to PSU Airflow

S5000, Service Side Kit, 2x AC PSU, 2x Fan Modules, PSU to I/O Airflow

S5000, Service Side Kit, 2x DC PSU, 2x Fan Modules, I/O to PSU Airflow

S5000, Service Side Kit, 2x DC PSU, 2x Fan Modules, PSU to I/O Airflow

Miscellaneous

S5000, Modular I/O Bay Blank Faceplate

Software

Software, OS9: Dell Networking Operating System, Layer 3 Software License

Software, OS9: iSCSI Optimized Configuration, Software License

Software, OS9: FCoE Transit Optimized Configuration

Software, DNOS: FCoE fabric and NPV Proxy Gateway (NPG), Software License

I/O Modules

S5000, 12-Port Ethernet/FCoE Module 1/10GbE/10GBase-T Interconnect

S5000, 12-Port Ethernet/FCoE Module, 1/10GbE SFP+ Interconnect

S5000, 12-Port Unified Port Module, 2/4/8Gbps Native Fibre Channel or 10GbE SFP+ Interconnect

Optics

Transceiver, QSFP+, 40GbE, SR Optics, 850nm Wavelength, 100–150m Reach on OM3/OM4

Transceiver, QSFP+, 40GbE, eSR Optics, 850nm Wavelength, 300–400m Reach on OM3/OM4

Transceiver, 40GbE QSFP+ to 1G Cu SFP adaptor, QSA

Transceiver, SFP+, 10GbE, SR, 850nm Wavelength, 300m Reach

Transceiver, SFP+, 10GbE, SR, 850nm Wavelength, 300m Reach, 12-pack

Transceiver, SFP+, 10GbE, LR, 1310nm Wavelength, 10km Reach

Transceiver, SFP+, 10GbE, ER, 1310nm Wavelength, 40km Reach

Transceiver, SFP+, 10GbE, LRM (Long Reach Multimode) Optic, 1310nm Wavelength, 220m Reach on MMF

Transceiver, SFP+, 8Gbps, Fibre Channel-SW, 150m Reach

Transceiver, SFP+, 8Gbps, Fibre Channel-SW, 150m Reach, 12-pack

Transceiver, SFP+, 8Gbps, Fibre Channel-LW, 4km Reach

Cables

Cable, 40GbE MTP to 4xLC 5M Optical Breakout Cable (optics not included)

Cable, 40GbE QSFP+ to 4xSFP+ 5M Direct Attach Breakout Cable

Cable, 40GbE QSFP+, Active Fibre Optic, 10m

Cable, 40GbE QSFP+, Active Fibre Optic, 50m

Cable, 40GbE QSFP+, Direct Attach Cable, 1m

Cable, 40GbE QSFP+, Direct Attach Cable, 5m

Cable, 40GbE QSFP+ to 4 x 10GbE SFP+, Active Optical Breakout Cable.

Cable, SFP+, CU, 10GbE, Direct Attach Cable, 0.5m

Cable, SFP+, CU, 10GbE, Direct Attach Cable, 1m

Cable, SFP+, CU, 10GbE, Direct Attach Cable, 3m

Cable, SFP+, CU, 10GbE, Direct Attach Cable, 5m

Cable, SFP+, CU, 10GbE, Direct Attach Cable, 7m

Cable, SFP+ to SFP+, 10GbE, Active Optical Cable, 15m

Note: Contact Dell for a more comprehensive SKU list

Physical

Four module slots (Optional Ethernet module or Unified port module)

4 x 40GbE fixed QSFP+ or 1/10GBase-T ports

48 x 1/10GbE SFP+ with additional 16 x 10GbE SFP+ port

12 x FC 2, 4 or 8Gbps ports

1 RJ45 console/management port with RS232 signaling

Size : 1RU, 1.71 x 17.4 x 28 in (4.4 mm x 441 mm x 711 mm)

Weight: 34 lbs (15.42 kg)

ISO 7779 A-weighted sound pressure level: 59.6 dBA at 73.4°F (23°C)

Power supply: 100 to 240 VAC 50/60 Hz or -48 to -60 VDC

Max. thermal output: 1878 BTU/hr

Max. current draw per system:

- 7A at 100/120 VAC, 3.5A at 200/240 VAC
- 15.2A at -46 VDC, 11.7A at -60 VDC

Max. power consumption: 550 Watts

Typical power consumption: 250 Watts

Max operating specifications:

- Operating temperature: 32°F to 104°F (0°C to 40°C)
- Operating humidity: 10 to 85% (RH), non-condensing

Max non-operating specifications:

- Storage temperature: -40°C to 158°C (-40°C to 70°C)
- Storage humidity: 5 to 95% (RH), non-condensing

High-Availability

Hot swappable redundant power supplies

Hot swappable redundant fans

Field replaceable I/O modules

Performance

MAC addresses: 128K

ARP table: 16K

IPv4 routes: 128K

IPv6 routes: 32K

Switch fabric capacity:

- 1.28Tbps (full-duplex)
- 640Gbps (half-duplex)

Forwarding capacity: 960Mpps

Link aggregation: 8 links per group, 128 groups per stack

Queues per port: 4 queues

VLANs: 4K

Line-rate layer 2 switching: All protocols, including IPv4

Line-rate layer 3 routing: IPv4

IP ACL: Ingress 1023; egress: 716

ACLs: 2K ingress, 1K egress

LAGs:	128 with up to 16
LAG load balancing:	Based on layer 2, IPv4 headers
Packet buffer memory:	9MB
CPU memory:	2GB
FCoE VLANs (Fabric Mode):	1
FCoE VLANs (NPV Mode):	12
FCoE VLANs (FSB Mode):	8
Jumbo Frames:	12,000 bytes

IEEE Compliance

802.1AB	LLDP
802.1ag	Connectivity Fault Management
802.1D	Bridging, STP
802.1p	L2 Prioritization
802.1Q	VLAN Tagging, Double VLAN Tagging, GVRP
802.1s	MSTP
802.1w	RSTP
802.1X	Network Access Control
802.3ab	Gigabit Ethernet (1000BASE-T)
802.3ac	Frame Extensions for VLAN Tagging
802.3ad	Link Aggregation with LACP
802.3ae	10 Gigabit Ethernet (10GBASE-X)
802.3ba	40 Gigabit Ethernet (40GBASE-SR4, 40GBASE-CR4) on Optical Ports
802.3u	Fast Ethernet (100BASE-TX) on Management Ports
802.3x	Flow Control
802.3z	Gigabit Ethernet (1000BASE-X)

ANSI/TIA-1057 LLDP-MED Force10 PVST+ MTU 12,000 bytes

RFC and I-D Compliance

General Internet protocols

768	UDP	854	Telnet
793	TCP	959	FTP

General IPv4 protocols

791	IPv4	1918	Address Allocation for Private Internets
792	ICMP		Diffserv Field in IPv4 and Ipv6 Headers
826	ARP	2474	
1027	Proxy ARP		
1035	DNS (client)	2596	Assured Forwarding PHB Group
1042	Ethernet Transmission	3164	BSD Syslog
1305	NTPv3	3195	Reliable Delivery for Syslog
1519	CIDR		
1542	BOOTP (relay)	3246	Expedited Assured Forwarding
1812	Requirements for IPv4 Routers	4364	VRF-Lite (IPv4 VRF with OSPF, BGP, IS-IS and v4 multicast VRRP

General IPv6 protocols

1981	Path MTU Discovery Features
2460	Internet Protocol, Version 6 (IPv6) Specification
2464	Transmission of IPv6 Packets over Ethernet Networks
2711	IPv6 Router Alert Option
4007	IPv6 Scoped Address Architecture
4213	Basic Transition Mechanisms for IPv6 Hosts and Routers
4291	IPv6 Addressing Architecture
4443	ICMP for IPv6
4861	Neighbor Discovery for IPv6
4862	IPv6 Stateless Address Autoconfiguration
5095	Deprecation of Type 0 Routing Headers in IPv6

IPv6 Management support (telnet, FTP, TACACS, RADIUS, SSH, NTP)

VRF-Lite (IPv6 VRF with OSPFv3, BGPv6, IS-IS)

Security

2404	The Use of HMAC-SHA-1-96 within ESP and AH	4250, 4251, 4252, 4253, 4254	SSHv2
2865	RADIUS	4301	Security Architecture for IPSec
3162	Radius and IPv6	4302	IPSec Authentication Header
3579	Radius support for EAP	4303	ESP Protocol
3580	802.1X with RADIUS	4807	IPSec Security Policy DB MIB
3768	EAP		
3826	AES Cipher Algorithm in the SNMP User Base Security Model		

RIP	RIPv1	2453	RIPv2
1058	OSPF (v2/v3)	4552	Authentication/Confidentiality for OSPFv3
1587	NSSA		
2154	OSPF Digital Signatures		
2328	OSPFv2		
2370	Opaque LSA	5340	OSPF for IPv6

BGP

1997 Communities

2385 MD5

2545 BGP-4 Multiprotocol Extensions for IPv6 Inter-Domain Routing

2439 Route Flap Damping

2796 Route Reflection

2842 Capabilities

2858 Multiprotocol Extensions

2918 Route Refresh

3065 Confederations

4360 Extended Communities

4893 4-byte ASN

5396 4-byte ASN representations

draft-ietf-idr-bgp4-20 BGPv4

draft-michaelson-4byte-as-representation-05 4-byte ASN Representation (partial)

draft-ietf-idr-add-paths-04.txt ADD PATH

Multicast

1112 IGMPv1

2236 IGMPv2

3376 IGMPv3

MSDP

draft-ietf-pim-sm-v2-new-05 PIM-SMw

Network convergence

802.1Qbb Priority-Based Flow Control

802.1Qaz Enhanced Transmission Selection (ETS)

Data Center Bridging eXchange (DCBx)

DCBx Application TLV (iSCSI, FCoE)

Fibre Channel over Ethernet (FCoE)

iSCSI over DCB (lossless iSCSI)

RDMA over Converged Ethernet (RoCE)

Fibre Channel (requires license)

Fibre Channel Forwarding (FCF)

NPV Proxy Gateway (NPG)

Fibre Channel port types: F, E, NP, VF

Bridging to FC SAN

Up to 12 FCoE_Maps per switch

Fabric Shortest Path First (FSPF)

Name server

Zoning

FCoE features (requires license)

FC-BB-5 support

Native FCoE forwarding

FCoE Initialization Protocol (FIP) v1

Connectivity to FIP Snooping Bridge

FCoE Transit (FIP Snooping Bridge)

FCoE to FC Forwarding

Dynamic FCoE to FC Load Balancing

Network management

1155	SMlv1
1157	SNMPv1
1212	Concise MIB Definitions
1215	SNMP Traps
1493	Bridges MIB
1850	OSPFv2 MIB
1901	Community-Based SNMPv2
2011	IP MIB
2096	IP Forwarding Table MIB
2578	SMlv2
2579	Textual Conventions for Smlv2
2580	Conformance Statements for Smlv2
2618	RADIUS Authentication MIB
2665	Ethernet-Like Interfaces MIB
2674	Extended Bridge MIB
2787	VRRP MIB
2819	RMON MIB (groups 1, 2, 3, 9)
2863	Interfaces MIB
3273	RMON High Capacity MIB
3410	SNMPv3
3411	SNMPv3 Management Framework
3412	Message Processing and Dispatching for the Simple Network Management Protocol (SNMP)
3413	SNMP Applications
3414	User-based Security Model (USM) for SNMPv3
3415	VACM for SNMP
3416	SNMPv2
3417	Transport mappings for SNMP
3418	SNMP MIB
3434	RMON High Capacity Alarm MIB
3584	Coexistence between SNMP v1, v2 and v3
4022	IP MIB
4087	IP Tunnel MIB
4113	UDP MIB
4133	Entity MIB
4292	MIB for IP
4293	MIB for IPv6 Textual Conventions
4502	RMONv2 (groups 1,2,3,9)
5060	PIM MIB
ANSI/TIA-1057 LLDP-MED	MIB
DelLITA_Rev.1.1	MIB
draft-grant-tacacs-02 TACACS+	
draft-ietf-idr-bgp4-mib-06 BGP Mibv1	
IEEE 802.1AB LLDP	MIB
IEEE 802.1AB LLDP DOT1	MIB
IEEE 802.1AB LLDP DOT3	MIB
sFlow.org sFlowv5	
sFlow.org sFlowv5 MIB (version 1.3)	
FORCE10-BGP4-V2-MIB	Force10 BGP MIB (draft-ietf-idr-bgp4-mibv2-05)
FORCE10-IF-EXTENSION-MIB	
FORCE10-LINKAGG-MIB	
FORCE10-COPY-CONFIG-MIB	
FORCE10-PRODUCTS-MIB	
FORCE10-SS-CHASSIS-MIB	
FORCE10-SMI	
FORCE10-TC-MIB	
FORCE10-TRAP-ALARM-MIB	
FORCE10-FORWARDINGPLANE-STATS-MIB	

Regulatory compliance

Safety

UL/CSA 60950-1, Second Edition

EN 60950-1, Second Edition

IEC 60950-1, Second Edition Including All National Deviations and Group Differences

EN 60825-1 Safety of Laser Products Part 1: Equipment Classification Requirements and User's Guide

EN 60825-2 Safety of Laser Products Part 2: Safety of Optical Fibre Communication Systems

FDA Regulation 21 CFR 1040.10 and 1040.11

Emissions

Australia/New Zealand: AS/NZS CISPR 22: 2006, Class A

Canada: ICES-003, Issue 4, Class A

Europe: EN 55022: 2006+A1:2007 (CISPR 22: 2006), Class A

Japan: VCCI V3/2009 Class A

USA: FCC CFR 47 Part 15, Subpart B:2011, Class A

Immunity

EN 300 386 V1.4.1:2008 EMC for Network Equipment

EN 55024: 1998 + A1: 2001 + A2: 2003

EN 61000-3-2: Harmonic Current Emissions

EN 61000-3-3: Voltage Fluctuations and Flicker

EN 61000-4-2: ESD

EN 61000-4-3: Radiated Immunity

EN 61000-4-4: EFT

EN 61000-4-5: Surge

EN 61000-4-6: Low Frequency Conducted Immunity

RoHS

All S Series components are EU RoHS compliant.

Certifications

Available with US Trade Agreements Act (TAA) compliance

USGv6 Host and Router Certified on Dell Networking OS 9.5 and greater

IPv6 Ready for both Host and Router

UCR DoD APL (core and distribution ALSAN switch)

Learn more at Dell.com/Networking.

September 2015 | Version 1.9
dell-networking-s series-s5000-spec sheet

© 2015 Dell Inc. All rights reserved. Dell, the DELL logo and the DELL badge are trademarks of Dell Inc. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Dell disclaims proprietary interest in the marks and names of others. This document is for informational purposes only. Dell reserves the right to make changes without further notice to the products herein. The content provided is as-is and without expressed or implied warranties of any kind.

