



Dell PowerEdge T710

The Dell™ PowerEdge™ T710 provides outstanding performance, availability and value in a 2S tower server for enterprise, remote workgroups, and growing businesses.

The Dell PowerEdge T710 features include the performance of Intel® Xeon® processor 5500 and 5600 series, the availability of up to 16 hard drive discs, DDR3 memory, excellent I/O capacity, and available redundant power.

The PowerEdge T710 was developed with a purposeful design—energy-optimized technology, advanced virtualization capabilities and simplified systems management.

Purposeful design

The PowerEdge T710 takes advantage of Dell's outstanding system commonality and reliability. Consistent component layout and purposeful placement of interface ports and power supplies enable easy installation and redeployment. The PowerEdge T710 purposeful design provides a standard LCD screen positioned by the front of the bezel for ease of monitoring.

Robust, metal hard drive carriers and organized cabling are designed to improve component access and airflow across the server. Designed for easy rack installation, the PowerEdge T710 offers an all-steel cable management arm to help eliminate creep.

Energy-optimized technology

Energy efficiency is designed at the system level on the PowerEdge T710 to help reduce power consumption while increasing performance capacity. Improvements include enhanced power supply units, an efficient fan design, and policy-driven power management.

Energy Smart 90%+ efficient power supply units are provided on the PowerEdge T710. A robust fan cage design with a single pull fan module helps improve airflow and enable fast, easy maintenance. Power Management features include power capping, power inventory, and power budgeting to best manage power in your specific environment.

Advanced virtualization

Featuring Intel® Xeon® processors 5500 series, embedded hypervisors, and expanded memory and I/O, Dell servers offer better overall system performance and virtual machine-per-server capacity than ever before.

Dell provides a smart path to virtualization that is grounded in choice and defined by industry standards. Choose your hypervisor from market leaders such as VMware® and Microsoft®, enabling virtualization with a few mouse clicks.

March 2013

Simplified systems management

The next-generation of Dell OpenManage™ suite of management tools is designed to provide efficient operations and standards-based commands designed to integrate with existing systems for effective control.

Dell Management Console (DMC) helps simplify operations and create stability by shrinking infrastructure management to one console. This console delivers a single view and a common data source into the entire infrastructure management. Built on Symantec™ Management Platform, it has an easily extensible, modular foundation that can provide basic hardware management or more advanced functions, such as asset and security management. Dell Management Console is designed to reduce or eliminate manual processes, enabling you to save time and money for more strategic technology usage.

Secure and efficient, the Dell Lifecycle Controller delivers "Instant On" integrated manageability through a single access point. The Unified Server Configurator (USC) interface enables persistent access to the tool because it is embedded and integrated into the system for significant flexibility and capabilities. The Lifecycle Controller is a one-stop shop for deploying operating systems with built-in driver installations, BIOS and firmware update and rollback, hardware configuration, and diagnostics.

Inspired by IT professionals, the PowerEdge T710 is rackable as a 5U and ideal for server consolidation.

Feature	PowerEdge T710 technical specification
Form factor	Tower or 5U rack
Processors	Latest quad-core or six-core Intel® Xeon® 5500 and 5600 series processors
Processor sockets	2
Front Side Bus (FSB) or HyperTransport	Intel QuickPath Interconnect (QPI)
Cache	4MB and 8MB
Chipset	Intel 5520
Memory ¹	Up to 288GB (18 DIMM slots): 1GB/2GB/4GB/8GB/16GB DDR3 up to 1333MT/s
I/O slots	6 PCIe G2 slots + 1 storage slot: Four x8 slots One x4 slot One x16 slot One x8 storage slot
RAID controller	<p>Internal: PERC H200 (6Gb/s) PERC H700 (6Gb/s) with 512MB battery-backed cache; 512MB, 1GB non-volatile battery-backed cache SAS 6/iR PERC 6/i with 256MB battery-backed cache PERC S100 (software based) PERC S300 (software based)</p> <p>External: PERC H800 (6Gb/s) with 512MB of battery-backed cache; 512MB, 1GB non-volatile battery-backed cache SAS 6/iR PERC 6/E with 256MB or 512MB of battery-backed cache</p> <p>External HBAs (non-RAID): 6Gbps SAS HBA SAS 5/E HBA LSI2032 PCIe SCSI HBA</p>
Drive bays	16 x 2.5" hard-drive option or 8 x 3.5" hard-drive option Two media bays support optical drives and/or Tape Backup Unit
Maximum internal storage ¹	Up to 24TB
Hard drives	Hot-plug hard drive options: 2.5" SAS SSD, SATA SSD, SAS (15K, 10K), nearline SAS (7.2K), SATA (7.2K) 3.5" SAS (15K, 10K), nearline SAS (7.2K), SATA (7.2K)
Communications	<p>Dual embedded Broadcom® NetXtreme II™ 5709c Gigabit Ethernet NIC with failover and load balancing (4 total ports); TOE (TCPIP Offload Engine) on Microsoft® Windows Server® 2003, SP1 or higher with Scalable Networking Pack Intel Ethernet X520 DA2 Dual-Port 10 Gigabit Server Adapter</p> <p>Optional 1GbE and 10GbE add-in NICs: Broadcom NetXtreme II 57711 Dual Port Direct Attach 10Gb Ethernet PCI-Express Network Interface Card with TOE and iSCSI Offload Intel Gigabit ET Dual Port Server Adapter and Intel Gigabit ET Quad Port Server Adapter Dual Port 10GB Enhanced Intel Ethernet Server Adapter</p> <p>X520-DA2 (FCoE Ready for Future Enablement) Brocade® CNA dual-port adapter Emulex® CNA iSCSI HBA stand up adapter OCE10102-IX-D Emulex CNA iSCSI HBA stand up adapter OCE10102-FX-D</p> <p>Optional add-in HBAs: Brocade FC4 and 8 GB HBAs</p>
Power supply	Two hot-plug redundant PSUs–1100 Watts
Availability	DDR3, hot-plug hard drives; optional hot-plug redundant power supplies; dual embedded NICs with failover and load balancing support (4 total ports); optional PERC6/i integrated daughtercard controller with battery-backed cache; hot-plug redundant cooling; toolless chassis; fibre and SAS cluster support; validated for Dell/EMC SAN
Video	Integrated Matrox® G200
Remote management	iDRAC6, Optional iDRAC6 Enterprise
Systems management	Dell™ OpenManage™
Rack support	ReadyRails™ sliding rails with optional cable management arm for 4-post racks (optional adapter brackets required for threaded hole racks)
Operating systems	<p>Microsoft® Windows Server® 2012 Microsoft Windows® Small Business Server 2011 Microsoft Windows Small Business Server 2008 Microsoft Windows Server 2008 SP2, x86/x64 (x64 includes Hyper-V®) Microsoft Windows Server 2008 R2 SP1, x64 (includes Hyper-V v2) Microsoft Windows HPC Server 2008 Novell® SUSE® Linux Enterprise Server Red Hat® Enterprise Linux®</p> <p>Virtualization options: Citrix® XenServer® VMware® vSphere® ESX™ and ESXi™ Red Hat Enterprise Virtualization®</p> <p>For more information on the specific versions and additions, visit Dell.com/OSsupport.</p>
Featured database applications	Microsoft SQL Server® solutions (see Dell.com/SQL) Oracle® database solutions (see Dell.com/Oracle)

¹ GB means 1 billion bytes and TB equals 1 trillion bytes; actual capacity varies with preloaded material and operating environment and will be less.

Dell Services

Dell Services can help reduce IT complexity, lower costs, and eliminate inefficiencies by making IT and business solutions work harder for you. The Dell Services team takes a holistic view of your needs and designs solutions for your environment and business objectives while leveraging proven delivery methods, local talent, and in-depth domain knowledge for the lowest TCO.

Simplify your servers at Dell.com/PowerEdge

© 2013 Dell Inc. All rights reserved. Dell, the DELL logo, the DELL badge, PowerEdge, ReadyRails, and OpenManage are trademarks of Dell Inc. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Dell disclaims proprietary interest in the marks and names of others. This document is for informational purposes only. Dell reserves the right to make changes without further notice to any products herein. The content provided is as is and without express or implied warranties of any kind.

