

High-powered.

Establishing a new performance standard in its class, the Wyse 3020 thin client provides an exceptional user experience at a highly affordable price. It features a dual core ARMADA 1.2GHz System-on-Chip (SoC) along with a built-in hardware media processor and delivers smooth imagery, bi-directional audio and flash playback performance. The 3020 thin client offers great functionality with support for up to two digital displays, a dual-band WiFi option* and Microsoft RemoteFX certification for high-end graphics.

Easy to use and manage.

The Wyse 3020 thin client arrives ready to connect to Citrix®, Microsoft®, VMware®, and Dell Wyse vWorkspace right out of the box. It is available in two virus-resistant firmware configurations - as a Citrix zero client with Wyse ThinOS Lite, or as a thin client with Wyse ThinOS.

IT won't need to visit or touch Wyse 3020 thin clients to manage them as they can be managed remotely with Wyse Device Manager (WDM). WDM offers remote enterprise-wide management that scales as you grow from just a few to tens of thousands of endpoints.

Compact. Energy-efficient.

Designing smooth playback of high bitrate HD video and graphics in such a small box hasn't been at the expense of energy consumption and heat emissions either. Using just 7 watts of electricity earns this device an Energy Star V5.0 rating. In addition, the 3020's small size enables discrete mounting options: under desks, to walls, and behind monitors, creating cool workspaces in every respect.

Specifications Dell Wyse 3020 Thin Client CPU Marvell® ARMADA™ Dual Core PXA2128 1.2 GHz system-on-chip (SoC) **Operating System** Wyse ThinOS Lite, Wyse ThinOS™ Memory 4GB Flash / 2GB DDR3 RAM Graphics Integrated in SoC, including support for Citrix HDX 3D and Microsoft RemoteFX One DVI-I port, DVI to VGA (DB-15) adapter included. One DVI-D port. I/O peripheral support Native dual digital display support with DVI-I and DVI-D ports. Four USB 2.0 ports, 3 in front, 1 in back 10/100/1000 Base-T Gigabit Ethernet. Networking Optional 802.11 a/b/g/n internal wireless, dual radio and dual antenna @ 300 Mbps* Single: up to 1920x1200@60Hz; color depth: 8, 16, 25, or 32 bpp Dual: up to 1920x1200@60Hz; color depth: 8, 16, 25, or 32 bpp Display Dual monitor supported with display rotation ("L shaped" displays) VESA monitor support with Display Data Control (DDC) for automatic setting of resolution and refresh rate Composite audio jack: 1/8-inch mini, 16-bit stereo. Audio Internal mono speaker. **Dimensions** Height: 1.38 in (35 mm) Width: 6.94 in (176 mm) Depth: 4.75 in (121 mm) Weight 1.1 lbs. (0.5 kg) Mountings Horizontal stand. The same stand can be used for VESA wall mounting. Security protocols supported for both wireless and 802.1x network based Security authentication: EAP-TLS; EAP-LEAP; EAP-PEAP, EAP-MSCHAPv2, EAP-GTC; WEP; WPA Personal; WPA2 Personal; WPA Enterprise; WPA2 Enterprise Worldwide auto-sensing 100-240 VAC, 50/60 Hz Energy Star V5.0 **Power** Phase V external and EuP compliant power adapter Average power usage with device connected to 1 keyboard with 1 mouse and 1 monitor: under 7.2 watts Horizontal position: 50° to 95° F (10° to 35° C) Temperature range Vertical position, power button up: 50° to 104° F (10° to 40° C); Storage: 14° to 140° F (-10° to 60° C) Humidity 20% to 80% condensing. 10% to 95% non-condensing Ergonomics: German EKI-ITB 2000, ISO 9241-3/-8 Safety: cULus 60950, TÜV-GS, EN 60950 Safety certifications RF Interference: FCC Class B, CE, VCCI, C-Tick Environmental: WEEE, RoHS Compliant Warranty Three-year limited hardware warranty. Complete services portfolio including Deployment Services, ProSupport and Accidental Damage service. Support and deployment *Wireless option is available in select countries **Kensington slot is not available with dual antenna configuration

Learn more: Visit www.dell.com/wyse

Dell Inc. One Dell Way Round Rock, TX 78664 Visit our website at: www.dell.com/wyse

Ask a Dell expert:

https://marketing.dell.com/t2d-wyse

Dell Cloud Client-Computing Sales 1-800-438-9973 CCC_sales@dell.com