

DELL™ AX4-5 STORAGE ARRAY



Combining simplicity and scalability, the Dell AX4-5 storage arrays deliver performance, expandability, and advanced data management features in a single, easy-to-use storage solution.

SIMPLE, SCALABLE, AND AFFORDABLE

The AX4-5 arrays combine easy-to-use features with the scalability of advanced storage arrays. The AX4-5 can support up to 64 hosts and up to 60 drives across four enclosures to provide the headroom that will keep up with your data growth.

FLEXIBLE CONNECTIVITY AND TIERED STORAGE TO MEET YOUR NEEDS

The AX4-5 enables organizations to choose a network interconnect that is right for their environment. AX4 iSCSI arrays support cost-effective IP networks, while Fibre Channel arrays utilize high-performance 4Gb/s connections. The AX4-5 can also easily mix SAS drives geared for performance with SATA drives that deliver cost-effective capacity.

EXCEPTIONAL DATA AVAILABILITY AND RELIABILITY

The AX4-5 has inherited many of the advanced software capabilities that have been available on the more advanced CX3 arrays. Its controllers provide end-to-end data integrity as well as continuous background disk consistency checking.

EASE-OF-USE FOR SIMPLE DEPLOYMENT AND MANAGEMENT

The AX4-5 comes with Navisphere® Express, an intuitive user interface that simplifies installation and operation and allows users to allocate new capacity in seconds.

OPTIONAL ADVANCED MANAGEMENT AND DATA REPLICATION SOFTWARE*

The optional Navisphere® Manager Suite can help meet the needs of growing and distributed organizations. Users can manage multiple Dell/EMC arrays from a single console. EMC® SnapView™ offers point-in-time snapshots and full-volume copies of critical data. For Fibre Channel models, EMC® MirrorView™ and SAN Copy™ enable data replication and migration between arrays.

DELL SIMPLIFIES IT SERVICES

Dell takes a customer-led approach, grounded in the philosophy that you know your business better than anyone. Dell offers services from infrastructure consulting and deployment to enterprise support.

*Anticipated availability in Q1 2008

DELL AX4-5 STORAGE ARRAY	
Array Overview	
Base models	AX4-5F with single or dual Fibre Channel controllers AX4-5I with single or dual iSCSI controllers
Cache	2G on dual controller models 1G on single controller models
RAID Levels	1/0, 3, 5
Supported Servers	All dual and quad socket Dell™ PowerEdge™ servers; Variety of Compaq®, HP®, IBM® and SUN® servers as validated by EMC®
OS Support	Microsoft® Windows® 2000 Server, Windows® Server™ 2003, Windows Server™ 2008 (when available), Linux®, Solaris™, VMware®, AIX, HP-UX, and limited Netware® support
Number of Supported Hosts	Up to 4 hosts directly connected; Up to 2 HA hosts directly connected Up to 64 HA hosts connected in a SAN
Front End Connectivity	AX4-5F: two 4Gbs Fibre Channel ports / controller (up to two controllers per array) AX4-5I: two 1Gbs iSCSI ports / controller (up to two controllers per array)
Disk Drives	
Storage Capacity	Up to 24TB with 400GB SAS drives Up to 45TB with 750GB SATA drives Up to 60TB with 1TB SATA Drives (Anticipated availability in Q1 2008)
Number of Disks	Each disk processing enclosure supports 12 drives Each disk expansion enclosure supports 12 drives Up to 4 expansion enclosures can be supported per array Up to 60 drives in the storage array
Drive Interface	Dual ported SAS with one 4X SAS expansion port per controller
Drives Available	146GB 15K RPM SAS drive 400GB 10K RPM SAS drive 750GB 7200 RPM SATA II 300GB 15K RPM SAS drive (Anticipated availability in Q1 2008) 1TB 7200 RPM SATA II drive (Anticipated availability in Q1 2008)
Array Software	
Integrated Software	Navisphere® Express Management Utility; EMC® PowerPath® for path failover for continuous data access and load balancing; Integrated snapshot capability
Optional Software	Navisphere® Manager; Navisphere® Analyzer; SnapView™ for point-in-time copy MirrorView™ (Fibre Channel only) for remote mirroring; SAN Copy™ (Fibre Channel only) for data migration between arrays

	AX4-5 DPE	AX4-5 DAE	STANDBY POWER
Dimensions			
Height	2U	2U	1U
Width	17.5 in. (44.45 cm)	17.5 in. (44.45 cm)	17.5 in. (44.45 cm)
Depth	20 in. (50.8 cm)	20 in. (50.8 cm)	24 in. (70 cm)
Weight	61 lb. (27.7 kg) max.	54 lb. (24.5 kg) max.	47 lb. (21.4 kg)
Operating Environment			
Power	450W	360W	20W
Heat Dissipation	1535 BTU/hr	1228 BTU/hr	21 BTU/hr
Operating Temp.	50°-104°F (10°-40°C)	50°-104°F (10°-40°C)	50°-104°F (10°-40°C)
Humidity	20-80% non-condensing	20-80% non-condensing	20-80% non-condensing
Altitude 8000 ft	104°F (40°C) max.	104°F (40°C) max.	104°F (40°C) max.
Altitude 10000 ft	98.6°F (37°C) max.	98.6°F (37°C) max.	98.6°F (37°C) max.

Dell cannot be responsible for errors in typography or photography. Dell disclaims proprietary interest in the marks and names of others. Dell is a trademark of Dell Inc. ©2008 Dell Inc. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. All rights reserved. Reproduction in any manner whatsoever without the express written permission of Dell Inc. is strictly forbidden. For more information contact Dell, December 2008.

SIMPLIFY YOUR NETWORK AT DELL.COM/EMC

