

# ENERGY STAR® Power and Performance Data Sheet

Dell PowerEdge R610 featuring the High-output 717W Power Supply



## System Characteristics

Form Factor	1U
Available Processor Sockets	2
Available DIMM Slots / Max Memory Capacity	12/96GB
ECC and/or Fully Buffered DIMMs	Yes
Available Expansion Slots	2 PCI-E
Minimum and Maximum # of Hard Drives	0 to 6
Redundant Power Supply Capable?	Yes
Power Supply Make and Model	Dell Energy Smart A717P-00
Power Supply Output Rating <sup>1</sup> (watts)	717
Minimum and Maximum # of Power Supplies	1 or 2
Input Power Range (AC or DC)	100-240VAC
Power Supply Efficiency at Specified Loadings <sup>1</sup>	77.2%@10%, 85.6%@20%, 90.6%@50%, 90%@100%
Power Supply Power Factor at Specified Loadings <sup>1</sup>	0.80@10%, 0.84@20%, 0.98@50%, 0.99@100%
Operating Systems Supported <sup>2</sup>	Microsoft Windows® Server 2003 and 2008 Microsoft Windows Essential Business Server 2008 Microsoft Windows Small Business Server 2008 Red Hat Enterprise Linux 4 and 5 Citrix XenServer 5.x <sup>3</sup> Vmware ESXi 3.5 <sup>3</sup> SUSE Linux Enterprise Server 10 and 11
Installed Operating System for Testing	Microsoft Windows Server 2003

1. Power supply information is for a single power supply only.
2. Available operating systems as shipped configurations from the factory.
3. Minimum as shipped configuration is installed SD disk.

## System Configurations

	Minimum	Typical	Maximum
Configuration ID			
Processor Information	1, Intel Xeon 5504	2, Intel Xeon 5540	2, Intel Xeon 5570
Memory Information	1 DIMM, 1GB	6 DIMMs, 2GB each	12 DIMM, 8GB each
Internal Storage	1 HDD	4 HDDs	6 HDDs
I/O Devices	4 onboard 1GB NIC ports	minimum + 1 dual port 1GB PCI-E NIC	minimum + 2 dual port 1GB PCI-E NIC
Power Supply Number and Redundancy Configuration	1	2	2
Management Controller or Service Processor Installed?	Yes	Yes	Yes
Other Hardware Features / Accessories	iDRAC6, SAS6/iR	iDRAC6, PERC6/i	iDRAC6, PERC6/i

## Power Data

	Minimum	Typical	Maximum
Idle Category (1S and 2S only)	Category D: Managed Dual Installed Processor (2P) Servers		
ENERGY STAR Idle Power Allowance (1S and 2S only)	69	218	408
Measured Idle Power (watts)	66.7	123.0	157.3
Power at Full Load <sup>1</sup> (watts)	103.4	269.3	291.1
Benchmark / Method Used for Full Load Test	Sandra Dhrystone isse 4.2		
Test Voltage and Frequency for Idle and Full Load Test	115V/60Hz		
Range of Total Estimated Energy Usage <sup>2</sup> (kWh/year)	1,169 to 1,812	2,155 to 4,718	2,756 to 5,099
Link to Detailed Power Calculator (if available)	<a href="http://WWW.Dell.com/CALC">WWW.Dell.com/CALC</a>		

1. Full load power represents the sustained, average power at 100% load of the given workload, and does not necessarily represent the absolute peak power or the highest average, sustained power possible for other workloads.
2. Estimated kWh/year gives the absolute range of energy use you could expect from continuous operation (24x7x365) and ranges from 100% idle usage to 100% full-load operation. The calculation also includes typical data center overhead at a ratio of 1 watt of overhead to every 1 watt of IT load (corresponding to a PUE of 2.0). Closer approximations may be found by using established power calculators and specific information about the intended operating environment (e.g., average time at Idle, data center PUE, etc.).

## Power and Performance for Benchmark #1

	Minimum	Typical	Maximum
Benchmark Used and Type of Workload	Sandra Dhrystone isse 4.2		
Avg. Power Measured During Benchmark Run	103.4	269.3	291.1
Benchmark Performance Score	41	122	143
Power Performance Ratio (perf score/avg. power)	0.4	0.45	0.49
Link to Full Benchmark Report (Where Available)			

Benchmark #1

## ENERGY STAR Power and Performance Data Sheet

Dell PowerEdge R610 featuring the High-output 717W Power Supply

Page 2 of 3



### Power Saving Features

	<i>Enabled on Shipment</i>	<i>End-User Enabling Required</i>
Processor Dynamic Voltage and Frequency Scaling	Yes	No
Processor or Core Reduced Power States	Yes	No
Power Capping	Yes	Yes
Variable Speed Fan Control Based on Power or Thermal Readings	Yes	No

### Power and Temperature Measurement and Reporting

Input Power Available & Accuracy?	Yes, +/- 5% for 20%-100% of max PSU load
Input Air Temp Available & Accuracy?	Yes, +/- 2%
Processor Utilization Available?	Yes
Other Data Measurements Available & Accuracy?	
Compatible Protocols for Data Collection	IPMI
Averaging method and time period	Power: 1min running average of 2s interval samples. Temperature: no averaging, 5s interval sampling.

### Thermal Information<sup>1</sup>

	<i>Minimum</i>	<i>Typical</i>	<i>Maximum</i>
Total Power Dissipation (watts)	138.0	285.0	425.0
Delta Temperature at Exhaust at 35C Peak Temp. (°C)	5.9 (9.7 at nominal temp)	10.9 (26.3 at nominal temp)	15.3 (30.0 at nominal temp)
Airflow at Maximum Fan Speed (CFM) at 35C Peak Temp.	42 (1CPU/6fan when managed, else 50)	47 (1CPU/7fan when managed, else 56)	50 (1CPU/7fan when managed, else 56)
Airflow at Nominal Fan Speed (CFM) at 25C Nominal Temp.	16	16	26

1. ASHRAE Extended Environmental Envelope Final August 1, 2008. Thermal Guidelines for Data Processing Environments, ASHRAE, 2004, ISBN 1-931862-43-5. Peak temperature is defined as 35 °C, Nominal Temperature is defined as 18 - 27 °C