



Dell PowerConnect J-SRX240

Dell™ PowerConnect™ J-SRX Series are secure routers that provide essential capabilities that connect, secure, and manage work force locations sized from handfuls to hundreds of users. By consolidating fast, highly available switching, routing, security, and applications capabilities in a single device, enterprises can economically deliver new services, safe connectivity, and a satisfying end user experience. All Dell PowerConnect J-SRX Series secure routers, including products scaled for the branch, campus and data center applications, are powered by Junos® OS—the established operating system that provides consistency, outstanding performance with services, and superb infrastructure protection at a low total cost of ownership.

J-SRX Series Secure Routers provide perimeter security, content security, access control, and network-wide threat visibility and control. State-of-the-art firewall and VPN technologies secure the perimeter with minimal configuration and consistent performance. By using zones and policies, even new network administrators can configure and deploy Dell PowerConnect J-SRX Series for the branch quickly and securely.

Policy-based VPNs support complex security architectures that require dynamic addressing and split tunneling. For content security, the J-SRX Series offers a comprehensive suite of Unified Threat Management (UTM) services consisting of intrusion prevention system (IPS), antivirus, antispam, Web filtering and data loss prevention via content filtering to protect your network from the latest content borne threats. Select models feature Content Security Accelerator for high-performance IPS and antivirus performance.

Select models in the J-SRX family feature serial, T1/E1, xDSL, and third generation (3G) cellular wireless options for WAN or Internet connectivity to securely link your sites. A variety of form factors allow you to make cost-effective choices for mission-critical deployments. Managing the network is easy using the established Junos OS command-line interface (CLI) and scripting capabilities, or an easy to use Web-based GUI.

The Dell PowerConnect J-SRX Series integrates with other security products to deliver enterprise-wide unified access control and adaptive threat management. These capabilities give security professionals powerful tools in the fight against cybercrime and data loss.

Dell PowerConnect J-SRX Series Secure Routers

Unified Threat Management
services for the distributed
Enterprise

Feature	Dell™ PowerConnect™ J-SRX240
Maximum Performance and Capacity	
Firewall performance (large packets)	1.5 Gbps
Firewall performance (IMIX)	500 Mbps
Firewall + routing PPS (64 Byte)	200 Kpps
AES256+SHA-1/3DES+SHA-1 VPN performance	250 Mbps
IPsec VPN Tunnels	1,000
IPS (intrusion prevention system)	250 Mbps
Antivirus	85 Mbps
Connections per second	9,000
Maximum concurrent sessions	64 K / 128 K
DRAM options	512 MB / 1 GB DRAM
Maximum security policies	4096
Maximum users supported	Unrestricted
Network Connectivity	
Fixed I/O	16 x 10/100/1000BASE-T
I/O slots	4 x SRX Mini-PIM
Services and Routing Engine slots	No
ExpressCard slot (3G WAN)	No
WAN/LAN interface options	See ordering information
Optional maximum number of PoE ports	Up to 16 ports of 802.3af/at with maximum 150 W
USB	2
IPsec VPN	
Concurrent VPN tunnels	1,000
Tunnel interfaces	128
DES (56-bit), 3DES (168-bit) and AES (256-bit)	Yes
MD-5 and SHA-1 authentication	Yes
Manual key, Internet Key Exchange (IKE), public key infrastructure (PKI) (X.509)	Yes
Perfect forward secrecy (DH Groups)	1,2,5
Prevent replay attack	Yes
Dynamic remote access VPN	Yes
IPsec NAT traversal	Yes
Redundant VPN gateways	Yes
Firewall	
Network attack detection	Yes
DoS and DDos protection	Yes
TCP reassembly for fragmented packet protection	Yes
Brute force attack mitigation	Yes
SYN cookie protection	Yes
Zone-based IP spoofing	Yes
Malformed packet protection	Yes

Feature	Dell™ PowerConnect™ J-SRX240
Unified Threat Management¹	
Intrusion Prevention System (IPS)	Yes
Protocol anomaly detection	Yes
Stateful protocol signatures	Yes
Intrusion prevention system (IPS) attack pattern obfuscation	Yes
Customer signatures creation	Yes
Frequency of updates	Daily and emergency
Antivirus	
Express AV (packet-based AV)	Yes
File-based antivirus	Yes
Signature database	Yes
Protocols scanned	POP3, HTTP, SMTP, IMAP, FTP
Antispyware	Yes
Antiadware	Yes
Antikeylogger	Yes
Antispam	Yes
Integrated Web filtering	Yes
Redirect Web filtering	Yes
Content filtering	Yes
Based on MIME type, file extension, and protocol commands	Yes
Dimensions and Power	
Dimensions (W x H x D)	17.5 x 1.75 x 15.1 in (44.4 x 4.4 x 38.5 cm)
Weight (Device and Power supply)	11.2 lb (5.1 kg) Non-PoE / 12.3 lb (5.6 kg) PoE No interface modules
Rack mountable	Yes, 1 RU
Power supply (AC)	100–240 VAC, 150 W Non PoE / 350 W PoE
Maximum PoE power	150 W
Average power consumption	61 W (LM), 65 W (HM), 179 W (PoE)
Input frequency	50-60 Hz
Maximum current consumption	1.0 A @ 100 VAC for (LM) 1.1 A @ 100 VAC for (HM) 3.0 A @ 100 VAC for (PoE)
Maximum inrush current	40 A for LM/HM, 45 A for PoE
Average heat dissipation	208 BTU/Hr (SRX240B) 222 BTU/Hr (SRX240H) 249 BTU/Hr (SRX240H-PoE)
Maximum heat dissipation	344 BTU/Hr (SRX210B) 369 BTU/Hr (SRX210H) 413 BTU/Hr (SRX210H-PoE)
Redundant power supply (hot swappable)	No
Acoustic noise level (Per ISO 7779 Standard)	54.1 dB

¹Unified Threat Management- antivirus, antispam, Web filtering and IPS require a subscription license and the high memory system option to use the feature. UTM is not supported on the low memory version. Please see the ordering section for options. Content Filtering and UAC are part of the base software with no additional license.

© 2010 Dell Inc. All rights reserved. Dell, the DELL logo, the DELL badge and PowerEdge are trademarks of Dell Inc. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Dell disclaims proprietary interest in the marks and names of others. This document is for informational purposes only. Dell reserves the right to make changes without further notice to the products herein. The content provided is as-is and without expressed or implied warranties of any kind.

Juniper Networks and Junos are trademarks or registered trademarks of Juniper Network, Inc. in the United States, other countries or both.

[Learn more at Dell.com/PowerConnect-J-Series](http://Dell.com/PowerConnect-J-Series)

