

Third-party information brought to you courtesy of Dell.



## Product Brief

Intel® 10 Gigabit AT  
Server Adapter  
Network Connectivity

# Intel® 10 Gigabit AT Server Adapter

## 10 Gigabit BASE-T Ethernet Server Adapters Designed for Multi-Core Processors and Optimized for Virtualization

### 10 Gigabit Performance at the Low Cost of Copper

The Intel® 10 Gigabit AT Ethernet Server Adapter showcases Intel's first-generation standards-based 10BASE-T adapter in a low-profile PCI Express\* form factor. It provides bandwidth-intensive applications highly affordable 10 Gigabit Ethernet (GbE) network performance with cost-effective RJ-45 connections for distances up to 100 meters. High-speed server connectivity – once reserved for costly, proprietary technologies such as High Performance Computing (HPC) clusters and grid-based computing – can now be achieved with the standardized connectivity of the Intel 10 Gigabit AT Server Adapter. Intel's adapter also provides 1000BASE-T support for gigabit connections to legacy switches.

### Next-Generation 10 Gigabit Performance

10 Gigabit Ethernet has moved past the early adoption stage and is rapidly becoming mainstay for backbones within enterprise and service provider networks. The escalating deployments of servers with multi-core processors and demanding applications such as HPC, database clusters, and video on demand are driving the need for 10 Gigabit connections. Based on the Intel® 82598EB 10 Gigabit Ethernet Controller, this next-generation Intel 10 Gigabit AT Server Adapter is designed to meet the throughput requirements of bandwidth-hungry applications.



### Performance-Enhancing Features for Multi-Core Environments

When implemented within multi-core processor environments, the Intel 10 Gigabit AT Server Adapter offers advanced networking features for efficient distribution of Ethernet workloads across CPU cores. Load balancing of interrupts using MSI-X enables more efficient response times and application performance. CPU utilization can be lowered further through stateless offloads such as TCP segmentation offload, header replications/splitting, and Direct Cache Access (DCA).

The Intel 10 Gigabit AT Server Adapter is optimized for virtualized environments, supporting multiple queues, alleviating I/O bottlenecks between virtual machines. Virtual Machine Device Queue (VMDq) technology offloads data sorting and data copying from the Virtual Machine Monitor (VMM) software layer to the hardware, improving overall throughput and CPU utilization on virtualized servers. Additionally, the Intel 10 Gigabit AT Server Adapter enables Intel® I/O Acceleration Technology<sup>1</sup> (Intel® I/OAT) with support for Intel® QuickData Technology for faster I/O processing on the new Quad-Core and Dual-Core Intel® Xeon® processor-based servers.



Conserve valuable PCI Express (PCIe\*) server slots while adding 10 Gigabit Ethernet capability with the Intel 10 Gigabit AT Server Adapter. The dedicated input/output (I/O) bandwidth of PCIe ensures priority performance on each port – without bus sharing – for 10 Gigabit Ethernet connectivity, as well as a low-profile design, which improves server throughput and rack density at the same time. In addition, eight-lane PCIe enables maximum bandwidth for fast and efficient data transfer.

## Advances for Storage Over Ethernet

The fast growth in storage capacity coupled with server virtualization has brought the need for Storage Area Network (SAN) to the forefront. To satisfy this growing demand, Intel 10 Gigabit AT Server Adapters support iSCSI acceleration through Intel I/OAT and provide advanced features for unified networking. Fast and reliable networked storage can be achieved via native iSCSI support with Microsoft, Linux\*, and VMware operating systems as well as support for iSCSI remote boot.

## Order Codes

Single unit EXPX9501AT

## Companion Products

Consider these Intel® products in your server and network planning:

- Intel® 10 Gigabit Server Adapters for PCI and PCI Express interfaces
- Intel® PRO/1000 Server Adapters
  - Copper or fiber-optic network connectivity, up to four ports per card
  - Solutions for PCI Express, PCI-X,\* and PCI interfaces
- Intel® PRO/1000 Desktop Adapters for PCI Express and PCI interfaces
- Other Intel® PRO Desktop and Server Adapters
- Intel® Xeon® Processors
- Intel® Server Boards

## Features

## Benefits

Intel® 82598EB 10 Gigabit Ethernet Controller	<ul style="list-style-type: none"> <li>▪ Industry-leading, energy-efficient design for next-generation 10 Gigabit performance and multi-core processors</li> </ul>
Low-profile	<ul style="list-style-type: none"> <li>▪ Enables higher bandwidth and throughput from standard and low-profile PCIe slots and servers</li> </ul>
Load balancing on multiple CPUs	<ul style="list-style-type: none"> <li>▪ Increases performance on multi-processor systems by efficiently balancing network loads across CPU cores when used with Receive-Side Scaling from Microsoft or Scalable I/O on Linux*</li> </ul>
Intel® I/OAT <sup>1</sup>	<ul style="list-style-type: none"> <li>▪ Accelerates I/O with higher throughput and lower CPU utilization by offloading processing overhead</li> </ul>
iSCSI remote boot support	<ul style="list-style-type: none"> <li>▪ Provides centralized Storage Area Network (SAN) management at a lower cost than competing iSCSI solutions</li> </ul>
MSI-X support	<ul style="list-style-type: none"> <li>▪ Minimizes the overhead of interrupts</li> <li>▪ Allows load balancing of interrupt handling between different cores/CPU's</li> </ul>
Virtual Machine Device queues (VMDq)	<ul style="list-style-type: none"> <li>▪ Allows the efficient routing of packets to the correct target machine in a virtualized environment using multiple hardware queues</li> <li>▪ Ensures transmit fairness and prevents head-of-line blocking</li> </ul>
Low latency	<ul style="list-style-type: none"> <li>▪ Ability to toggle between the interrupt aggregation and non-aggregation mode based on the type of data being transferred</li> </ul>
Optimized queues: 32 Transmit (Tx) and 64 Receive (Rx) per port	<ul style="list-style-type: none"> <li>▪ Enhances network performance and reduces CPU utilization in the virtualized environment</li> <li>▪ Reduces I/O overhead on the hypervisor in a virtualized server by performing data sorting and coalescing in the network silicon</li> </ul>
Network packet handling without waiting or buffer overflow	<ul style="list-style-type: none"> <li>▪ Efficient packet prioritization</li> </ul>
Support for most Network Operating Systems (NOS)	<ul style="list-style-type: none"> <li>▪ Enables widespread deployment</li> </ul>
Compatible with x8 and x16 standard and low-profile PCI Express* slots	<ul style="list-style-type: none"> <li>▪ Allows each PCI Express* slot port to operate without interfering with the other</li> </ul>
Remote management support	<ul style="list-style-type: none"> <li>▪ Reduces support costs with remote management based on industry-wide standards</li> </ul>
RJ-45 connections over category-6A cabling	<ul style="list-style-type: none"> <li>▪ Ensures compatibility with cable lengths up to 100 meters</li> </ul>
RoHS-compliant <sup>2</sup> lead-free <sup>3</sup> technology	<ul style="list-style-type: none"> <li>▪ Compliant with the European Union directive (effective as of July 2006) to reduce the use of hazardous materials</li> </ul>
Intel® PROSet Utility for Microsoft Windows* Device Manager	<ul style="list-style-type: none"> <li>▪ Provides point-and-click power over individual adapters, advanced adapter features, connection teaming, and Virtual Local Area Network (VLAN) configuration</li> </ul>
Intel backing	<ul style="list-style-type: none"> <li>▪ Backed by an Intel limited lifetime warranty, 90-day money-back guarantee (U.S. and Canada), and worldwide support</li> </ul>

# Specifications

## General

Product codes	EXPX9501AT
Connectors	RJ-45 Copper
Cabling	Category-6A

## Adapter Product Features

Intel® PROSet Utility for easy configuration and management	▪
Intel® lead-free <sup>3</sup> technology	▪
Plug and play specification support	Standard
Intel® I/OAT <sup>1</sup> including QuickData	▪
Includes a full-height bracket	▪
RoHS <sup>2</sup>	▪
Cabling Distance	
10BASE-T	100 m on Cat-6A, 55 m on Cat-6
1000BASE-T	100 m on Cat-5e, Cat-6 or Cat-6A
Receive-side scaling	▪
VMdQ <sup>4</sup>	In a virtualized environment, packets dedicated to different virtual machines can be routed to different queues, thus easing the routing of these packets to the target machine
Advanced packet filtering (per port)	<ul style="list-style-type: none"> <li>▪ 16 exact-matched packets (unicast or multicast)</li> <li>▪ 4096-bit hash filter for multicast frames</li> <li>▪ Promiscuous (unicast and multicast) transfer mode support</li> <li>▪ Optional filtering of invalid frames</li> </ul>
Direct Cache Access (DCA)	The I/O device activates a pre-fetch engine in the CPU that loads the data into the CPU cache ahead of time, before use, eliminating cache misses and reducing CPU load

## Network Management

Wired for Management (WfM) baseline v2.0 enabled for servers	▪
DMI 2.0 support, Windows Management Instrumentation (WMI) and SNMP	▪
Remote Installation Services (RIS)	▪
PXE 2.0 enabled through boot Read-Only Memory (ROM)	▪

## Network Operating Systems (NOS) Software Support

Microsoft Windows Server 2003*	▪
Microsoft Vista*	▪
Microsoft Windows Virtual Server 2005*	▪
Red Hat Enterprise 4* or later	▪
SUSE SLES 10* or later, Professional 9.2 or later	▪
FreeBSD 5.x* or later	▪
VMware ESX 3.x* support	▪
Fedora*	▪
EFI 1.1	▪

## Intel Backing

Limited lifetime warranty	▪
90-day, money-back guarantee (U.S. and Canada)	▪

## Advanced Software Features

Adapter Fault Tolerance (AFT)	▪
Switch Fault Tolerance (SFT)	▪
Adaptive Load Balancing (ALB)	▪
Teaming support	▪
IEEE 802.3ad <sup>5</sup> (link aggregation control protocol)	▪
PCIe Hot Plug/Active Peripheral Component Interconnect (PCI)	▪
IEEE 802.1Q VLANs	▪
IEEE 802.3 2005 flow control support	▪
Tx/Rx IP, TCP, & UDP checksum offloading (IPv4, IPv6) capabilities (Transmission control protocol (TCP), User Datagram Protocol (UDP), Internet Protocol (IP))	▪
IEEE 802.1p	▪
TCP segmentation/large send offload	▪
MSI -X supports Multiple Independent Queues	▪
Interrupt moderation	▪
IPv6 offloading	Checksum and segmentation capability extended to new standard packet type

## Technical Features

Data rate(s) supported per port	1 Gigabit and 10 Gigabit
Bus type	PCI Express 2.0 (2.5 Gt/s)
Bus width	x8 lane PCI Express, operable in x8 and x16 slots
Bus speed (x8, encoded rate)	20 Gbps uni-directional; 40 Gbps bi-directional
Interrupt levels	INTA, MSI, MSI-X
Hardware certifications	FCC B, UL, CE, VCCI, BSMI, CTICK, MIC
Controller-processor	Intel® 82598EB
Typical power consumption	24 W 100LFM
Operating temperature	0° C to 55° C (32° F to 131° F)
Storage temperature	-40° C to 70° C (-40° F to 158° F)
Storage humidity	90% non-condensing relative humidity at 35° C
LED Indicators	LINK (solid) and ACTIVITY (blinking)

## Physical Dimensions

Length	16.74 cm (6.59 in)
Width	6.89 cm (2.71 in)
Height of end bracket	PCI Express standard, 12 cm (4.725 in); PCI Express low-profile, 7.92 cm (3.12 in)

## Network-Ready Servers

Top PC and server manufacturers offer Intel® adapters in their new products. Specify or ask for Intel® Network Connections with your next PC, server, or mobile PC purchase. For a list of preferred suppliers, visit us at [www.intel.com/buy/networking/adapters.htm](http://www.intel.com/buy/networking/adapters.htm).

## Customer Support

Intel® Customer Support Services offers a broad selection of programs including phone support and warranty service. For more information, contact us at [support.intel.com/support/go/network/adapter/home.htm](http://support.intel.com/support/go/network/adapter/home.htm). Service and availability may vary by country.

## For Product Information

To speak to a customer service representative regarding Intel products, please call 1-800-538-3373 (U.S. and Canada) or visit [support.intel.com/support/go/network/contact.htm](http://support.intel.com/support/go/network/contact.htm) for the telephone number in your area. For additional product information on Intel Networking Connectivity products, visit [www.intel.com/network/connectivity](http://www.intel.com/network/connectivity).

To see the full line of Intel Network Adapters for PCI Express, visit [www.intel.com/network/connectivity](http://www.intel.com/network/connectivity) or contact your Dell Sales Representative.

The information contained in this document, including all instructions, cautions, and regulatory approvals and certifications, is provided by Intel and has not been independently verified or tested by Dell. Dell cannot be responsible for damage caused as a result of either following or failing to follow these instructions. All statements or claims regarding the properties, capabilities, speeds or qualifications of the part referenced in this document are made by Intel and not by Dell. Dell specifically disclaims knowledge of the accuracy, completeness or substantiation for any such statements. All questions or comments relating to such statements or claims should be directed to Intel. Visit [www.dell.com](http://www.dell.com) for more information.

<sup>1</sup>Intel® I/O Acceleration Technology (Intel® I/OAT) requires an operating system that supports Intel I/OAT.

<sup>2</sup>Lead and other materials banned in RoHS Directive are either (1) below all applicable substance thresholds the EU or (2) an approved/pending exemption applies.

<sup>3</sup>Lead has not been intentionally added, but lead may still exist as an impurity below 1000 ppm, or an approved RoHS exemption applies.

<sup>4</sup>Intel® VMDq requires an operating system that supports VMDq.

<sup>5</sup>Available only when used with a capable switch.

INFORMATION IN THIS DOCUMENT IS PROVIDED IN CONNECTION WITH INTEL® PRODUCTS. NO LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS IS GRANTED BY THIS DOCUMENT. EXCEPT AS PROVIDED IN INTEL'S TERMS AND CONDITIONS OF SALE FOR SUCH PRODUCTS, INTEL ASSUMES NO LIABILITY WHATSOEVER, AND INTEL DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY, RELATING TO SALE AND/OR USE OF INTEL PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. UNLESS OTHERWISE AGREED IN WRITING BY INTEL, THE INTEL PRODUCTS ARE NOT DESIGNED NOR INTENDED FOR ANY APPLICATION IN WHICH THE FAILURE OF THE INTEL PRODUCT COULD CREATE A SITUATION WHERE PERSONAL INJURY OR DEATH MAY OCCUR.

Intel may make changes to specifications and product descriptions at any time, without notice. Designers must not rely on the absence or characteristics of any features or instructions marked "reserved" or "undefined." Intel reserves these for future definition and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to them. The information here is subject to change without notice. Do not finalize a design with this information.

The products described in this document may contain design defects or errors known as errata which may cause the product to deviate from published specifications. Current characterized errata are available on request. Contact your local Intel sales office or your distributor to obtain the latest specifications and before placing your product order. Copies of documents which have an order number and are referenced in this document, or other Intel literature, may be obtained by calling 1-800-548-4725, or by visiting Intel's Web Site at <http://www.intel.com/>.

Copyright © 2008 Intel Corporation. All rights reserved. Intel, the Intel logo and Xeon are trademarks of Intel Corporation in the U.S. and other countries.

\*Other names and brands may be claimed as the property of others.

