



EqualLogic FS7600 and FS7610 NAS Appliances

Enhance your enterprise storage capabilities with scale-out unified storage

Improve productivity and streamline your IT infrastructure by storing block and file data on a single scale-out storage platform. The unique architecture behind the Dell™ EqualLogic™ PS Series arrays and the EqualLogic FS7600 and FS7610 NAS appliances helps you expand storage capacity and system performance non-disruptively as your needs evolve over time.

Scale-out unified storage optimized for midrange deployments

Unstructured file data is a large part of IT storage environments, and it's growing faster and faster. Whether it's for documents, images or file-based workflows, the amount of capacity required for file data continues to increase with no end in sight. But just adding disks to support that mountain of file data won't help.

The EqualLogic FS7600 and FS7610 (FS7600 Series) are key components of the Dell storage architecture, which puts the right information in the right place at the right time — for the right cost. These systems support both 1Gb Ethernet (FS7600) and 10Gb Ethernet with either SPF+ or BASE-T (FS7610) connectivity to the SAN and client network; plus, the 1GbE is upgradeable to 10GbE.

Unlike many unified storage solutions that only scale in capacity, the EqualLogic FS7600 and FS7610 with EqualLogic PS Series arrays can scale capacity and performance independently. To expand capacity, simply add more PS Series arrays — the EqualLogic FS7600 Series supports all new and existing EqualLogic arrays. To improve front-end file performance, two FS7600 or FS7610 NAS appliances can be joined in the same EqualLogic storage pool, while still providing a single namespace.

Next generation architecture provides an alternative to traditional file shares

The EqualLogic FS7600 Series appliances use the Dell Fluid File System (FluidFS), a scale-out distributed file system implemented across Dell Storage product lines. FluidFS is designed to optimize file access performance and is built on proven hardware. Capacity can easily be expanded across the entire storage backend, all within a single namespace. Administration is easy and unified for file and block protocols. A core technology of Dell storage architecture, FluidFS is a high-performance, enterprise-class file system that does not have strict limits on file system size and share size inherent in other NAS solutions. With FluidFS, the capacity needed to store common enterprise data can be dramatically decreased. Savings of up to 48%¹ are possible through policy-driven, variable-block deduplication and LZPS compression of the data. In addition, deduped data can be rehydrated on read, and thin provisioning technology enables efficient storage space allocation. These features are available to existing customers as part of the FluidFS upgrade; no extra hardware or licensing fees are required.

With the FS7600 Series, an EqualLogic group can serve up to 509TB of usable capacity for file storage, all within a single namespace. To help improve storage flexibility and utilization, the EqualLogic FS7600 Series features a virtualization layer that lets you expand NAS storage dynamically without any downtime.

Dell's NAS appliance provides a number of features including a highly available dual controller architecture in a single, 2U NAS appliance. This platform simplifies installation with less required cabling, enhances performance with a PCIe backplane for inter-controller communications, and improves dependability with cache mirroring and fully redundant hot-swappable primary components.

Advanced features, EqualLogic family values

In addition to block storage management, NAS deployment and management functionality are fully integrated into EqualLogic Group Manager, including administration, monitoring and maintenance operations. Group Manager automates the initial setup and configuration of your FS7600 Series appliance, simplifying the process of creating volumes and shares. An FS7600 Series NAS appliance can be configured and added to an EqualLogic Group quickly and efficiently.

In addition to a range of data protection features for block storage, the EqualLogic FS7600 Series NAS appliances include advanced file data protection features such as snapshots, replication, NAS container cloning, NDMP backup and CIFS antivirus integration. End users can restore previous versions of files either from a snapshot directory, or through the familiar Previous Versions dialog box in Windows Explorer without IT assistance. To keep the data on CIFS shares virus free, the appliances can be integrated with qualified anti-virus solutions, tested and supported by the FS7600 Series NAS appliance. In addition, Access Based Enumeration can ensure that users can only view the files and folders to which they have access to when browsing content on the NAS share. FluidFS v4 incorporates data management enhancements such as automated home shares and directory quotas. Also, FluidFS v4 includes protocol support for SMB 3.0, NFS v4 ACLs and NFS v4.1.

As with all EqualLogic products, the FS7600 Series NAS appliance's full feature set, software licensing and future firmware enhancements are included in the base price. This provides licensing simplicity, access to a comprehensive set of product features and ongoing value after initial purchase.

Features	EqualLogic FS7600/FS7610 with FluidFS v4
Cluster scalability	Up to two FS7600/FS7610 appliances (four controllers) in a single NAS cluster
File system capacity	Up to 509TB
1GbE configuration options	Two Intel 1GbE four-port NICs per controller Client connectivity over Ethernet, SAN connectivity over iSCSI Ethernet switch is required; direct connect to the SAN is not supported
10GbE configuration options	Two Intel 10GbE dual-port NICs per controller, copper or optical, SFP+ or 10GBASE-T standards Client connectivity over Ethernet, SAN connectivity over iSCSI Ethernet switch is required; direct connect to the SAN is not supported
Storage arrays supported	Any EqualLogic group running version 8.1 or later firmware
Management	EqualLogic Group Manager
NFS file protocol support	NFSv4.x and NFSv4 ACLs (for implementation detail, refer to the FluidFS support matrix)
SMB file protocol support	SMB 3.0 (for implementation detail, refer to the FluidFS support matrix)
NAS volumes	Max NAS volumes per NAS cluster: 1,024; max NAS volume size: as large as the file system/namespace
Shares/exports	Max number of SMB shares per cluster: 1,024; max number of NFS mounts/exports per cluster: 1,024
Multi-client subnet support	Configure multiple client networks and VLANs to present NFS exports or CIFS shares
Concurrent active SMB connections	Max for single appliance: 5,000; max for a two-appliance cluster: 10,000 ("active" defined as clients engaging in I/O in the last 15 minutes)
User authentication	For SMB clients: Kerberos v5 and NTLM v2 on Microsoft Active Directory Server; for NFS v4 clients: Kerberos 5 on AD and SASL support for encryption
Directory services	Windows SMB and NFS clients: Microsoft® Active Directory® 2003, 2003R2, 2008, 2008R2, 2012, 2012R2; Linux/UNIX clients: NIS and secured LDAP
Quotas	User and group quota rules per container: 1,000; max user quotas per cluster: 1,000
Local users	Max local users per cluster: 100; max local groups per cluster: 100
Directories	Max number of directories per cluster: 10 billion; max directory name length: 255 bytes
Files	Max file size: 16TB; max number of files per cluster: 10 billion; max file name length: 255 bytes
Snapshots	Redirect-on-write snapshots; max number of snapshots per container/cluster: 1,024/10,000; max number of snapshot policies per container/cluster: 512/1,024
Replication	Asynchronous to peer FS7610/FS7600/FS7500 appliances, dissimilar clusters cluster sizes only (client network speeds and array configurations can vary); max number of replication partners (or destinations): 100; max number of replication policies per cluster: 512; max number of concurrent replications: 10 outgoing, 100 incoming; max containers enabled for replication: 256
NDMP backup	Remote or three-way NDMP over Ethernet ports Certified with Dell Quest NetVault® Backup 9.10, CommVault® Simpana® 9.10, IBM® Tivoli® Storage Manager 6.3, Symantec™ NetBackup™ 7.0 and 7.5, Symantec Backup Exec™ 2012, 2014, EMC Networker 8.x
ICAP antivirus	Certified with Symantec ScanEngine 5.2 and Protection 7.0, 7.5, McAfee® Virus Scan® Enterprise 8.8 and Enterprise for Storage 1.1.0, Sophos Endpoint Security and Control 10.2, 10.3, TrendMicro™ InterScan Web Security Suite 3.1
Data reduction	Post-process policy-based variable block (128KB +/- 64KB) data deduplication and LZPS compression per NAS volume
Memory	24GB DDR3 1066MT/s per controller (48GB per appliance)
Power supply	Primary: two power supplies per appliance; backup: one battery per controller, two batteries per appliance
Input voltage	90-264 VAC; auto-ranging; this system is also designed to be connected to IT power systems with a phase to phase voltage not exceeding 230V
Output wattage	717W
Heat dissipation	2446 BTU/hr
Line frequency	47-63 Hz
Current	10.5Amp at 90 VAC steady state, 5.2Amp at 180 VAC steady state
Dimensions	Form factor: 2U; width: 44.63 cm (17.6 in) (does not include rack flange); depth: 81.30 cm (32.0 in) (includes bezel and controllers installed); height: 8.64 cm (3.4 in); weight max configuration: 30.5 kg (67 lb)

¹ Based on May 2013 internal Dell analysis of the FS8600 NAS appliance with Fluid Data Reduction, using real-world home share environment comprised of Office files (21%), .GZ (19%) and .flate (19%) files, among others.

² Requires EqualLogic Array Software 8.1.

End-to-end technology solutions

Reduce IT complexity, lower costs and eliminate inefficiencies by making IT and business solutions work harder for you. You can count on Dell for end-to-end solutions to maximize your performance and uptime. A proven leader in Servers, Storage and Networking, Dell Enterprise Solutions and Services deliver innovation at any scale. And if you're looking to preserve cash or increase operational efficiency, Dell Financial Services™ has a wide range of options to make technology acquisition easy and affordable. Contact your Dell Sales Representative for more information.**

Learn More at Dell.com/FS7600

©2015 Dell Inc. All rights reserved. Dell, the DELL logo, the DELL badge, and EqualLogic are trademarks of Dell Inc. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Dell disclaims proprietary interest in the marks and names of others. This document is for informational purposes only. Dell reserves the right to make changes without further notice to any products herein. The content provided is as is and without express or implied warranties of any kind. **Leasing and financing provided and serviced by Dell Financial Services L.L.C. or its affiliate or designee ("DFS") for qualified customers.

