

Product Use and Handling

Observe the Product Safety and other Regulatory information provided with your product, on product labeling, and provided on this website. In addition, observe the following use and handling guidelines to help prevent damage to your product:



- NOTICE:** When taking the product through temperature extremes, from low-temperature conditions into a warmer environment or from high-temperature conditions into a cooler environment, allow the product to acclimate to ambient use temperature and for any condensation that may have formed to evaporate before turning on power to avoid damage to the product.
- Protect your product from environmental hazards such as dirt, dust, food, liquids, temperature extremes, and overexposure to sunlight.
 - Clean the Portable or Personal Electronic Device (PED) display, monitor, LCD or television screen with a soft, clean cloth and water. Apply the water to the cloth, then stroke the cloth across the display in one direction, moving from the top of the display to the bottom. Remove moisture from the Portable or PED display or monitor quickly and keep the display or monitor dry. Exposure to moisture such as rain or a liquid spill can damage the product. Do not use a commercial window cleaner to clean your device.
 - Leave adequate clearance on all vented sides of the product to permit the airflow required for proper ventilation.
 - Do not restrict airflow into the product by blocking any vents or air intakes.
 - Clean any air vents on the front, back, and vented sides of the product. Lint, dust and other foreign materials can block the vents and restrict the airflow.
 - Do not operate the product in an enclosure that does not allow airflow unless adequate intake and exhaust ventilation are provided on the enclosure. Restricting the airflow impacts your product's performance, possibly causing it to overheat.
 - Leave a 10.2 cm (4 in) minimum clearance on all vented sides of the product to permit the airflow required for proper ventilation.
 - If your enclosure has doors, they need to be of a type that allows at least 30% airflow through the enclosure (front and back).
 - If your product has a modem RJ-11 connector and a network RJ-45 connector, which are similar in appearance, ensure that you insert the telephone cable into the RJ-11 connector, not the RJ-45 connector.
 - To help protect your AC mains powered product from sudden, transient increases and decreases in electrical power, use a surge suppressor, line conditioner, or uninterruptible power supply (UPS).